

Product data sheet

CONTEC Aluminium Rim "Xeta"



Description

The ideal foundation for building a tubeless-ready wheel for 29" bikes with 32 spokes. Thanks to its hollow-chamber construction, the Xeta Max aluminium rim, made of 6063 aluminum, is particularly lightweight and sturdy. When assembled into a complete wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 30 mm, tires ranging from 60 to 75 mm in width fit on the rim. The single-eyelet spoke holes ensure additional durability of the aluminium rim by reducing friction between the Spoke Nipples and the rim and also preventing the Nipples from grinding into the rim. The Xeta Max aluminium rim is only suitable for wheels with disc brakes. You can find compatible tubeless Rim Tape in our CONTEC product range.

Website



<https://www.contec-parts.com>

Article number: 03498164

Original number: 30006872

EAN: 4251971141124

EVP: 39.95 €

Technical data

Design	doublewall
Width	34.0 cm
Brake mounting	disc - Center Lock, disc - 5-hole, disc - 6-hole, roller brake, drum brake
Brake compatibility rim	disc
ETRTO	30-622
Main colour	black
For wheel	yes
Height	18.0 cm
Wheel size	28 / 29 "
Material 1	aluminium
Weight	0.595 kg
Text wheel configurator	suitable for E-bike
Valve type	Sclaverand (SV)
Permissible system weight	150 kg
Spoke Hole	easy eyelets
Brake track	no
Number of spoke holes	32 holes
Rim model	Xeta

Product data sheet

CONTEC Aluminium Rim "Xeta"

