

CLASSIC MEDUNA PT 5W-30 LA

Passenger car motor oil HC-synthetic based SAE 5W-30 low ash, specially for gas-powered vehicles and vehicles with service interval extension

Description

CLASSIC MEDUNA PT 5W-30 LA is an innovative synthetic engine oil based on synthetic hydrocracked (HC) oils suitable for all passenger cars. Produced according to the latest technology, **CLASSIC MEDUNA PT 5W-30 LA** contains only minimum heavy metals and offers great performance. This is of particular benefit to vehicles with exhaust gas purification systems such as particle filter and catalytic converters.

Extensive engine tests have shown that **CLASSIC MEDUNA PT 5W-30 LA** significantly prolongs the service life of particle filters. **CLASSIC MEDUNA PT 5W-30 LA** is also recommended for use in older vehicles of all emission standard classes. In exhaust gas turbochargers, **CLASSIC MEDUNA PT 5W-30 LA** causes virtually no deposits, which has a long-term optimising effect on the boost pressure. The combination of the advantageous SAE 5W-30 rating and the latest technology results in improved long-term fuel economy. The product's thermal stability and low sulphated ash levels keep the pistons clean, irrespective of the fuel used.

Application

CLASSIC MEDUNA PT 5W-30 LA meets the requirements of all vehicles equipped with modern exhaust gas purification systems. It is suitable for use in diesel, petrol and gas engines and can be mixed with other engine oils.

Properties

- excellent wear protection even under continuous load at maximum engine power
- universal oil for diesel, petrol and gas engines of new and older vehicles
- reduced exhaust gas emissions
- low oil consumption thanks to minimum evaporation loss
- reduces fuel consumption by approx. 3%

Product data

Properties	Unit	5W-30*
Density 15 °C	g/cm ³	0.85
Viscosity 40 °C	mm ² /s	72,9
Viscosity 100 °C	mm ² /s	12,3
Viscosity index		164
COC flash point	°C	215
Pour point	°C	-40

* are average values and may vary in the framework of the standard.

Quality level

API SN
ACEA C3
ILSAC GF-5

Performance

VW 505.01/505.00/502.00
MB 229.52/229.51/MB 229.31
PSA B71 2290

BMW Longlife-04
Opel/Vauxhall OV 0401547 - D30