WOLF OFFICIALTECH
0W-30 MS-BFE

29/10/2025
65660

This is an ACEA C2/C3 engine oil based on carefully selected very high quality base oils. This oil is specifically formulated to meet the BMW Longlife-19 FE engine oil specification.
It is adapted to meet the requirements of the latest technology, highly engineered turbo engines requiring high performance and lower viscosity oils.

APPLICATIONS

This ACEA C2/C3 and API SP engine oil is tailor made for the BMW Longlife-19 FE engine oil specification. It provides a multi vehicle application through the ACEA C2 specification. Optimum formulation for today's cars with exceptional film strength preventing oil film breakdown and reducing friction providing fuel economy and reliability.

FEATURES

Cold start: excellent fluidity at low temperature.
Fuel economy: superior fuel economy and CO2 reduction.
Total engine protection: performance in keeping the engine clean.

SPECIFICATIONS

ACEA	C2	MB	226.5
ACEA	C3	MB	229.31
API	SP	MB	229.51
BMW	LONGLIFE-04	OPEL	OV 040 1547 - D30
BMW	LONGLIFE-12FE	OPEL	OV 040 1547 - G30
BMW	LONGLIFE-19 FE	RENAULT	RN 0700
FIAT	9.55535-DS1	RENAULT	RN 0710
FIAT	9.55535-GS1		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.8419
Kinematic viscosity at 40°C	ASTM D445	mm²/s	66.91
Kinematic viscosity at 100°C	ASTM D445	mm²/s	12.15
Viscosity index	ASTM D2270		181
Pour point	ASTM D6892	°C	0
Sulfated Ash	ASTM D874	Mass %	0.8
Flash Point COC	ASTM D92	°C	230
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	9.1

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV