

The **NOMAD POWER 501** is a lithium-based power pack that combines 3 functions :

- **Booster for 12 V vehicles** (*motorbike, quad, car, SUV*).
- **Autonomous power supply for all kinds of electrical appliances.**
- **Emergency lamp.**

LITHIUM BATTERY BOOSTER

Its **lithium** battery ($LiCoO_2$) gives it an exceptional power-to-size ratio (*starting current: 500 A*).

It starts vehicles equipped with a discharged 12 V battery (*liquid, gel, AGM, Start&Stop*) in a few seconds (⚠ *do not start Lithium $LiFePO_4$ batteries with this booster, battery voltages not compatible*).

START										
12 V PETROL & DIESEL	5 > 90 Ah									

SAFETY START

The **smart jump lead** protects both the battery and the vehicle's electronics:

- Anti-spark technology,
- Short circuit protection,
- Reverse polarity protection,
- Protection against excessive starting currents,
- Protection against booster temperature increases.

MOBILE ENERGY SOURCE

Its storage capacity (*3 Ah*) gives it sufficient autonomy to meet the daily needs of staying connected (*telephone, tablet, computer*).

Equipped with:

- **2 USB ports** : 5 V / 9 V / 12 V - 2 A / 5 V - 2 A for recharging smartphone, tablet, GPS, etc.
- **1 output port 15 V - 5 A** ideal for powering a 12 V electrical appliance (*cool box, fan, etc.*)

HIGH BRIGHTNESS ASSIST LAMP

Auxiliary light (*1 led*) with 3 lighting modes: normal, strobe, SOS.

LCD DISPLAY

The **NOMAD POWER 501** is equipped with an LCD display that gives information on:

- the % of charge of the internal battery.
- the different input and output ports used.

A SMART PRODUCT

Lightweight (480 g) and compact, it will ideally find its place in a vehicle's glove box/tray as well as in a suitcase.




Colour LCD display



Supplied with case
+ accessories



Smart jump lead



Multiconnectors
USB cable



USB-C / USB-C
charging cable
















Charger unit optional



087101 USB charger 15 W



🇬🇧 087354 USB charger 15 W

STARTING						EQUIPMENT				INPUT / OUTPUT				POWER BANK	LED	DIMENSIONS	
Lithium			I			SMART CABLE	CABLES 			INPUT 	OUTPUT 						
Capacity per cell	Type	Full charge					Start	Cranking CC	Peak Battery		USB-C	MICRO USB Type B	Lightning				
3 Ah 45 Wh	LiCoO ₂	3 h 30	500 A	1000 A	1200 A					5V - 2A	2  5V - 2A 5/9/12V - 2A	—	5 A		3 modes : Light SOS SPOT	17.5 x 8.5 x 3	0.480