Product data sheet

CONTEC Aluminium Rim "Lexa" 28 / 29"



Website

https://www.contec-parts.com

Article number:	03498244
Original number:	81033203012FS
:	
EVP:	**33.95 €**

Description

CONTEC "Lexa" Aluminium Rim
Hollow-wall symmetrical, aluminum, 28", 19-622, for 2 mm spoke diameter, with silver brake flange, includes wear indicator
double-eyelet (silver), 596 mm ERD (measured including spoke holes), height: 21.5 mm, inner width: 19 mm, outer width: 24 mm, AV/DV valve, max. spoke tension 1200 N, max. system weight 150 kg, suitable for e-bikes, **32-hole, black**

Technical data

Design	doublewall
Brake mounting	no mount, disc - Center Lock, disc - 5-hole, disc - 6-hole, roller brake, drum brake
Brake compatibility rim	universal
ETRTO	19-622
Main colour	black
For wheel	yes
Wheel size	28 / 29 "
Material	aluminium
Valve type	Dunlop (DV), Schrader (AV)
Wear indicator	yes
Permissible system weight	150 kg
Spoke Hole	double eyelets
Colour brake track	silver
Hollow chamber shape	symmetrical
Rim height	22 mm
Rim inner width	19 mm
Rim outer width	24 mm
Spoke hole diameter	for 2.00 mm
Eyelet color	silver
Effective Rim Diameter	596 mm
max. spoke tension	1,200 N
Brake track	yes
Number of spoke holes	32 holes
Rim model	Lexa


This product data sheet is based on the information available at the time of generation. Subsequent changes to prices, technical specifications, or product information are possible. The current details provided with the item are authoritative.

Date of generation: 10.11.2026

Product data sheet

CONTEC Aluminium Rim "Lexa" 28 / 29"





This product data sheet is based on the information available at the time of generation. Subsequent changes to prices, technical specifications, or product information are possible. The current details provided with the item are authoritative.

Date of generation: 10.11.2026