#### **Product information**

## Top Tec 4210 SAE 0W-30

# LIQUI MOLY

#### **Description**

Top class fully synthetic, low-SAPS motor oil for superior performance and best engine efficiency. Designed for use in numerous Volkswagen and Audi vehicles and also suitable for use in a variety of BMW diesel, Mercedes-Benz as well as specific Porsche models, etc. Use with extended oil change intervals as per manufacturer.



#### **Properties**

- minimizes friction
- highest fuel economy
- optimum lubrication under all operating conditions
- excellent high-pressure and wear protection properties
- outstanding engine cleanliness
- reduces pollutant emissions
- instant lubrication after cold start
- increases service life
- ideal with particulate filters and catalytic converters
- tested for turbocharger

#### **Technical data**

Flash point 428 °F

DIN ISO 2592

Evaporation loss (Noack) 10,0 %

ASTM D5800 B

Total base number 8,4 mg KOH/g

PI 23/02/01/2024

**DIN ISO 3771** 

Sulfate ash 0,8 g/100g

DIN 51575

Color number (ASTM) L 2.5

**DIN ISO 2049** 

#### Specifications / Approvals

ACEA C3 • BMW Longlife-04 • MB-Approval 229.51 • MB-Approval 229.52 • Porsche C30 • VW 504 00 • VW 507 00

#### LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

API SN •

### Technical data

SAE Viscosity	0W-30 SAE J300
Density at 59 °F	0,845 g/cm³ DIN 51757
Viscosity at 104 °F	60,0 mm²/s ASTM D7042
Viscosity at 212°F	11,9 mm²/s ASTM D7042
Viscosity at -40 °F (MRV)	< 60000 mPas ASTM D4684
Viscosity at -31 °F (CCS)	< 6200 mPas ASTM D5293
HTHS at 302 °F	≽ 3,5 mPas ASTM D5481
Viscosity index	200 DIN ISO 2909

-54 °F DIN ISO 3016

#### Areas of application

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

#### **Application**

Observe the manufacturers instructions!

#### Available pack sizes

1 l Canister plastic 22156

USA-AND-CANADA-EN-F

5 l Canister plastic 22158

USA-AND-CANADA-EN-F

20 l Canister plastic 22160

USA-AND-CANADA-EN-F

60 l Black plate barrel 22161

USA-AND-CANADA-EN-F

205 l Black plate barrel 22162

USA-AND-CANADA-EN-F

1.000 l Container 22168

USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.

Pour point

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de