# Product data sheet

## BS-BATTERY Battery "BTX20-BS"




| | |
|---|---|
| **Article number:** | 05379771 |
| **Original number:** | 300611 |
| **EAN:** | 3661451001113 |
| **EVP:** | **114.37 €** |

### Technical data

| | |
|---|---|
| Design | MTF, with acid pack |
| Width | 87.0 mm |
| Range of application | motorcycle |
| Energy | 230.40 Wh |
| Bleeding | internal |
| Filling quantity | 0.9 l |
| Height | 155.0 mm |
| Cold start current CCA | 270 A |
| Capacity 10 Hr | 18.0 Ah |
| Capacity 20 Hr | 18.9 Ah |
| Length | 175.0 mm |
| Minus pole | front right |
| Plus pole | front left |
| Weight | 5.620 kg |
| Voltage | 12V |
| Screwing | M6 |

### Description

**BS-BATTERY Battery "BTX20-BS"**
ETN: 518 902 026, **BS battery, MTF**maintenance-free

Attach the acid pack supplied after removing the adhesive strip and allow to run evenly into all cells. Leave for about 1-2 hours and then press the sealing strip on firmly. Once filled, the battery is sealed and no further maintenance is necessary.
**Caution**Batteries from 12 V may require recharging! Never open or drill into these sealed (MTF) batteries or remove the sealing strip!

This product data sheet is based on the information available at the time of generation. Subsequent changes to prices, technical specifications, or product information are possible. The current details provided with the item are authoritative.

**Date of generation: 28.10.2026**