

**Safety data sheet
according to UK REACH**

Printing date 04.08.2025

Version: 9.01 (replaces version 9.00)

Revision: 04.08.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** SONAX Plastic Restorer - Black**Article number:**

04091000

UFI: 7WC5-30K3-1009-S1DP**1.2 Relevant identified uses of the substance or mixture and uses advised against****Application of the substance / the mixture**

Car care product

Lacquer

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Skin Sens. 1A H317 May cause an allergic skin reaction.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS07

Signal word Warning**Hazard-determining components of labelling:**

1,2-benzisothiazol-3(2H)-one

2-methylisothiazol-3(2H)-one

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

-GB-

Safety data sheet according to UK REACH

Printing date 04.08.2025

Version: 9.01 (replaces version 9.00)

Revision: 04.08.2025

Trade name: SONAX Plastic Restorer - Black

(Contd. of page 1)

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Pigmented acrylate dispersion

Dangerous components:

CAS: 112-34-5 EINECS: 203-961-6 Reg.nr.: 01-2119475104-44-xxxx	2-(2-butoxyethoxy)ethanol ----- Eye Irrit. 2, H319	3-<5%
CAS: 2682-20-4 EINECS: 220-239-6 Reg.nr.: 01-2120764690-50-xxxx	2-methylisothiazol-3(2H)-one ----- Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	<0.1%
CAS: 2634-33-5 EINECS: 220-120-9 Reg.nr.: 01-2120761540-60-xxxx	1,2-benzisothiazol-3(2H)-one ----- Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.036 %	>0.0015-<0.01%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:**

Remove soiled clothing

In any cases of doubt or if symptoms are present, seek medical advice.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Wash the areas of skin affected with water and a mild detergent.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed sensitization

Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

GB

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 04.08.2025

Version: 9.01 (replaces version 9.00)

Revision: 04.08.2025

Trade name: SONAX Plastic Restorer - Black

(Contd. of page 2)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Foam

Carbon dioxide

Fire-extinguishing powder

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Protective equipment:

The normal measures for firefighting are to be taken.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from ignition sources.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special precautions are necessary if used correctly.

Do not allow any product to enter drains, not even when cleaning the sponge. Dispose of product residue at your local collection point for hazardous waste.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Observe local/state/federal regulations.

Further information about storage conditions:

Keep container tightly sealed.

Store receptacle in a well ventilated area.

(Contd. on page 4)

GB

Safety data sheet according to UK REACH

Printing date 04.08.2025

Version: 9.01 (replaces version 9.00)

Revision: 04.08.2025

Trade name: SONAX Plastic Restorer - Black

(Contd. of page 3)

Protect from frost.
Recommended storage temperature: 5 - 35
7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

WEL (Great Britain)	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm
IOELV (EU)	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm
OEL (Ireland)	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm IOELV

Regulatory information

WEL (Great Britain): EH40/2020

IOELV (EU): (EU) 2019/1831

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

DNELs

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

Oral	DNEL	5 mg/kg bw/day (consumer) (chronic systemic effect)
Dermal	DNEL	83 mg/bw/day (worker) (chronic systemic effect)
	DNEL	50 mg/kg bw/day (consumer) (chronic systemic effect)
Inhalative	DNEL	67.5 mg/m ³ (worker) (chronic systemic effect)
	DNEL	67.5 mg/m ³ (worker) (chronic locale effects)
	DNEL	40.5 mg/m ³ (consumer) (chronic systemic effect)
	DNEL	40.5 mg/m ³ (consumer) (chronic locale effects)

PNECs

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

PNEC	200 mg/l (STP)
	11 mg/l (water)
	1.1 mg/l (water (fresh water))
	0.11 mg/l (water (sea water))
PNEC	4.4 mg/kg (sediment (fresh water))
	0.44 mg/kg (sediment (sea water))
	0.32 mg/kg (soil)
	56 mg/kg (water)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Hand protection Protective gloves

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 04.08.2025

Version: 9.01 (replaces version 9.00)

Revision: 04.08.2025

Trade name: SONAX Plastic Restorer - Black

(Contd. of page 4)

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove materialValue for the permeation: Level 6 (≥ 480 min)

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye/face protection Not required in normal cases

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Physical state**

Fluid

Colour:

Black

Odour:

Nearly odourless

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

Undetermined.

Flammability

Product is not flammable.

Lower and upper explosion limit**Lower:**

Not applicable

Upper:

Not applicable

Flash point:

Not applicable.

Auto-ignition temperature:

Not determined.

Decomposition temperature:

Not determined.

pH (100 g/l) at 20 °C

6-9

Viscosity:**Kinematic viscosity at 40 °C**>20.5 mm²/s**Solubility****water:**

Fully miscible.

Partition coefficient n-octanol/water (log value)

Not determined.

Vapour pressure at 50 °C:

100 hPa

Density and/or relative density**Density at 20 °C:**1.03-1.04 g/cm³**Vapour density**

Not determined.

9.2 Other information**Appearance:****Form:**

Fluid

Important information on protection of health and environment, and on safety.**Ignition temperature:**

Product is not selfigniting.

Explosive properties:

Product does not present an explosion hazard.

Solvent separation test:

<3 %(V)

VOC (EC)

126 g/l

Change in condition**Evaporation rate**

Not determined.

Information with regard to physical hazard classes**Explosives**

Void

Flammable gases

Void

Aerosols

Void

Oxidising gases

Void

Gases under pressure

Void

Flammable liquids

Void

Flammable solids

Void

Self-reactive substances and mixtures

Void

Pyrophoric liquids

Void

Pyrophoric solids

Void

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 04.08.2025

Version: 9.01 (replaces version 9.00)

Revision: 04.08.2025

Trade name: SONAX Plastic Restorer - Black

(Contd. of page 5)

Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid See Section 7 for information on safe handling.

10.5 Incompatible materials:

strong oxidizing agents

strong acids

strong alkali

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Oral	ATE	>2,000 mg/kg (calculated)
Dermal	ATE	>2,000 mg/kg (calculated)
Inhalative	ATE	>20 mg/l (calculated)

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

Oral	LD50	2,410 mg/kg (mouse) (ECHA)
Dermal	LD50	2,764 mg/kg (rabbit) (ECHA)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Additional toxicological information:

Repeated dose toxicity

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

Oral	NOAEL	250 mg/kg (rat) (ECHA)
Inhalative	NOAEC	0.094 mg/m ³ (rat) (OECD 413)

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 04.08.2025

Version: 9.01 (replaces version 9.00)

Revision: 04.08.2025

Trade name: SONAX Plastic Restorer - Black

(Contd. of page 6)

11.2 Information on other hazards**Endocrine disrupting properties**

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:**CAS: 112-34-5 2-(2-butoxyethoxy)ethanol**

LC50 / 96h	1,300 mg/l (Lepomis macrochirus) (OECD 203)
EC50 / 48h	>100 mg/l (Daphnia magna) (ECHA)
ErC50	1,101 mg/l (Pseudokirchneriella subcapitata) (ECHA)

CAS: 2682-20-4 2-methylisothiazol-3(2H)-one

EC 20 / 3h	2.8 mg/l (activated sludge) (DIN 38412-3 (TTC-Test))
EC50/3h	34.6 mg/l (activated sludge) (DIN 38412-3 (TTC-Test))

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

NOEL 21 d	1.2 mg/l (daphnia) (OECD 211)
LC50/4d	2.2 mg/l (Oncorhynchus mykiss) (OECD 203)
EC 20 / 3h	3.3 mg/l (sewage sludge)
EC50/3h	13 mg/l (sewage sludge)
NOEC / 28d	0.21 mg/l (Oncorhynchus mykiss) (OECD 215)
EC10 / 72 h	0.04 mg/l (Selenastrum capricornutum) (OECD 201)
EC50 / 2 d	3.27 mg/l (daphnia) (OECD 202)
EC50 / 3 d	0.11 mg/l (Selenastrum capricornutum) (OECD 201)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential**CAS: 2682-20-4 2-methylisothiazol-3(2H)-one**

BCF	3.16
log Kow	≤0.32

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

BCF	6.95 (fish) (OECD 305)
log Kow	0.7 (octan-1-ol/water (OECD 117))

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment**PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects**Additional ecological information:****General notes:**

The product may not be released into the environment without control.

Do not allow product to reach ground water, water course or sewage system.

GB

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 04.08.2025

Version: 9.01 (replaces version 9.00)

Revision: 04.08.2025

Trade name: SONAX Plastic Restorer - Black

(Contd. of page 7)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Do not allow any product to enter drains, not even when cleaning the sponge. Dispose of product residue at your local collection point for hazardous waste.

European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR/RID/ADN, IMDG, IATA	Void
14.3 Transport hazard class(es) ADR/RID/ADN, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Directives:

Directive 2010/75/EU (VOC) 0.88 %

Directive 2004/42/CE 32.0 g/l

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to
REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.
Annex II - REPORTABLE EXPLOSIVES PRECURSORS
None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning juveniles must be observed.

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 04.08.2025

Version: 9.01 (replaces version 9.00)

Revision: 04.08.2025

Trade name: SONAX Plastic Restorer - Black

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H301 Toxic if swallowed.
 H302 Harmful if swallowed.
 H311 Toxic in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008

Skin sensitisation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--------------------	--

Date of previous version: 25.06.2025

Version number of previous version: 9.00

Abbreviations and acronyms:

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

*** Data compared to the previous version altered.**