

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Beast Wheel cleaner

Article number:

04331000, 04333000, 04335000

UFI: SN25-F016-X00U-A5FQ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Car care product

Detergents

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS07

Signal word Warning

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing spray.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 22.04.2025

Version: 6.01 (replaces version 6.00)

Revision: 22.04.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 1)

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: aqueous tenside solution with additives

Dangerous components:

CAS: 367-51-1 EINECS: 206-696-4 Reg.nr.: 01-2119968564-24-xxxx	sodium mercaptoacetate solution (46%) ⚠ Acute Tox. 4, H302; Skin Sens. 1B, H317	15-<20%
CAS: 147170-44-3 EC No 931-333-8 Reg.nr.: 01-2119489410-39-xxxx	1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered, C18 unsaturated)) acyl derivs., hydroxides, inner salts Alternative CAS number: 61789-40-0 ⚠ Eye Dam. 1, H318; Aquatic Chronic 3, H412 Specific concentration limits: Eye Dam. 1; H318: C ≥ 10 % Eye Irrit. 2; H319: 4 % ≤ C < 10 %	1-<4%
CAS: 37971-36-1 EINECS: 253-733-5	2-phosphonobutane-1,2,4-tricarboxylic acid ⚠ Met. Corr. 1, H290; ⚠ Eye Irrit. 2, H319	1-<3%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

amphoteric surfactants, phosphonates, non-ionic surfactants	<5%
perfumes (EUCALYPTUS GLOBULUS OIL, MENTHOL)	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Induce vomiting only, if affected person is fully conscious.

Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

sensitization

Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

GB

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 22.04.2025

Version: 6.01 (replaces version 6.00)

Revision: 22.04.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 2)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Avoid contact with the eyes and skin.

For non-emergency personnel

The usual precautionary measures are to be adhered to when handling chemicals.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

Information about storage in one common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Protect from frost.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

GB

Safety data sheet according to UK REACH

Printing date 22.04.2025

Version: 6.01 (replaces version 6.00)

Revision: 22.04.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 3)

DNELs

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

Dermal DNEL 2.06 mg/kg (worker long-term systemic effects)

Inhalative DNEL 1.41 mg/kg (worker long-term systemic effects)

CAS: 147170-44-3 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered, C18 unsaturated)) acyl derivs., hydroxides, inner salts

Oral DNEL 7.5 mg/kg (consumer) (longterm systematic effects)

Dermal DNEL 7.5 mg/kg (consumer) (longterm systematic effects)

12.5 mg/kg (worker) (longterm systematic effects)

Inhalative DNEL 44 mg/m³ (worker) (longterm systematic effects)

PNECs

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

PNEC 0.038 mg/l (freshwater (Süßwasser))

0.0038 mg/l (water (sea water))

CAS: 147170-44-3 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered, C18 unsaturated)) acyl derivs., hydroxides, inner salts

PNEC 3,000 mg/l (STP)

0.0135 mg/l (water (fresh water))

0.00135 mg/l (water (sea water))

PNEC 1 mg/kg (sediment (fresh water))

0.1 mg/kg (sediment (sea water))

0.8 mg/kg (soil)

CAS: 37971-36-1 2-phosphonobutane-1,2,4-tricarboxylic acid

PNEC 0.666 mg/l (water (fresh water))

0.066 mg/l (water (sea water))

PNEC 50.4 mg/kg (sewage plant)

2.398 mg/kg (sediment (fresh water))

0.089 mg/kg (soil)

PNEC 0.24 mg/kg (sediment (sea water))

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Hand protection Protective gloves

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material

Value for the permeation: Level 6 (≥480min)

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

(Contd. on page 5)

GB

Safety data sheet according to UK REACH

Printing date 22.04.2025

Version: 6.01 (replaces version 6.00)

Revision: 22.04.2025

Trade name: SONAX Beast Wheel cleaner

Eye/face protection Not required in normal cases

(Contd. of page 4)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Fluid
Colour:	Black
Odour:	Fruit-like
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	100 °C (CAS: 7732-18-5 water)
Flammability	Product is not flammable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Auto-ignition temperature:	Not applicable.
Decomposition temperature:	Not determined.
pH at 20 °C	5-5.3
Viscosity:	
Kinematic viscosity at 40 °C	<20.5 mm²/s
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	23 hPa (CAS: 7732-18-5 water)
Density and/or relative density	
Density at 20 °C:	1.06-1.07 g/cm³
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Not corrosive to metals in line with 37.4 UN RTDG, handbook on test methods and criteria.

(Contd. on page 6)

GB

Safety data sheet according to UK REACH

Printing date 22.04.2025

Version: 6.01 (replaces version 6.00)

Revision: 22.04.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 5)

Desensitised explosives

Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.**10.2 Chemical stability** Stable under normal conditions.**10.3 Possibility of hazardous reactions** No dangerous reactions known.**10.4 Conditions to avoid** See Section 7 for information on safe handling.**10.5 Incompatible materials:** strong oxidizing agents**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:**

Oral	ATE	>2,000 mg/kg (Additivity formula)
Dermal	ATE	>5,000 mg/kg (Additivity formula)

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

Oral	LD50	>300 mg/kg (rat) (OECD 423 (Conc. 46%))
Dermal	LD50	1,000-2,000 mg/kg (rat) (OECD 402 (Conc. 98%))

CAS: 147170-44-3 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered, C18 unsaturated)) acyl derivs., hydroxides, inner salts

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

CAS: 37971-36-1 2-phosphonobutane-1,2,4-tricarboxylic acid

Oral	LD50	>2,000 mg/kg (rat) (EG-Richtlinie 92/69/EWG B.1)
Dermal	LD50	>4,000 mg/kg (rat)
	LD 50	>4,000 mg/kg (rat) (EU Method B.3)
Inhalative	LC50 / 4h	>1.979 mg/l (rat) (OECD 403)
	EC 10 / 72 h	>33-<66 mg/l (Desmodesmus subspicatus) (OECD 201)

Skin corrosion/irritation Based on available data, the classification criteria are not met.**Serious eye damage/irritation** Based on available data, the classification criteria are not met.**Respiratory or skin sensitisation** May cause an allergic skin reaction.**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**Additional toxicological information:****Repeated dose toxicity****CAS: 37971-36-1 2-phosphonobutane-1,2,4-tricarboxylic acid**

Oral	NOAEL	>5,000 ppm (rat) (OECD 408, 90d, target organ: liver)
	NOAEL 14d	>1,042 mg/kg (Danio rerio) (OECD 204)
	NOAEL	>1,000 mg/kg (rat) (OECD 414)

(Contd. on page 7)

GB

Safety data sheet according to UK REACH

Printing date 22.04.2025

Version: 6.01 (replaces version 6.00)

Revision: 22.04.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 6)

11.2 Information on other hazards

Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

LC50 / 96h	>100 mg/l (Oncorhynchus mykiss) (OECD 203 (Subs. thioglycolic acid))
LC50 / 48h	880 mg/l (Leuciscus idus) (DIN 38412 / 15 (Subs. thioglycolic acid))
EC50 / 48h	38 mg/l (Daphnia magna) (84/449/EWG (Subs. thioglycolic acid))
EC50 / 72h	13 mg/l (Pseudokirchneriella subcapitata) (OECD 201 (Subs. thioglycolic acid))

CAS: 147170-44-3 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered, C18 unsaturated)) acyl derivs., hydroxides, inner salts

LC 50	>1-10 mg/l (Pimephales promelas) (OECD 203)
EC0	>100 mg/l (Pseudomonas putida) (OECD 209)
EC50	>1-10 mg/l (Daphnia magna) (OECD 202)
	>1-10 mg/l (Desmodesmus subspicatus) (OECD 201)
NOEC	≤1 mg/l (Oncorhynchus mykiss) (OECD210)
	≤1 mg/l (Daphnia magna) (OECD 211)

CAS: 37971-36-1 2-phosphonobutane-1,2,4-tricarboxylic acid

LC50 / 96h	>1,042 mg/l (Danio rerio) (OECD 204)
EC50	>1,071 mg/kg (Daphnia magna) (OECD 202)
ErC 50 / 72h	>1,081 mg/l (Desmodesmus subspicatus) (OECD 201)
NOEC / 21 d	104 mg/l (Daphnia magna) (OECD 211)

12.2 Persistence and degradability

The surface-active substances contained in the product meet the requirement of the EU Detergent Regulation (EC/648/2004) for ultimate biodegradability for surfactants in detergents.

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

Biodegradation	67 % (28d OECD 301d (thioglycolic acid))
----------------	--

CAS: 37971-36-1 2-phosphonobutane-1,2,4-tricarboxylic acid

Biodegradation	0 % (activated sludge) (OECD301E/92/69/EWG, C4.-B)
	30-40 % (sludge) (OECD 302 A)

12.3 Bioaccumulative potential

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

log POW	>2.99 (20°C OECD 107 (thioglycolic acid))
---------	---

12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 22.04.2025

Version: 6.01 (replaces version 6.00)

Revision: 22.04.2025

Trade name: SONAX Beast Wheel cleaner

Danger to drinking water if even extremely small quantities leak into the ground.

(Contd. of page 7)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Not classified as hazardous waste according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

1) Disposal / product

2) Disposal / contaminated packaging

20 01 30 | detergents other than those mentioned in 20 01 29

15 01 02 | plastic packaging

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR/RID/ADN Void

IMDG, IATA Void

14.3 Transport hazard class(es)

ADR/RID/ADN, ADN, IMDG, IATA

Class Void

14.4 Packing group

ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user

Not applicable.

UN "Model Regulation": Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Directives:

Directive 2010/75/EU (VOC) not subject to

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Waterhazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.

(Contd. on page 9)

GB

Safety data sheet according to UK REACH

Printing date 22.04.2025

Version: 6.01 (replaces version 6.00)

Revision: 22.04.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 8)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Skin sensitisation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--------------------	--

Date of previous version: 08.01.2025

Version number of previous version: 6.00

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = Lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Met. Corr. 1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**