

## PETEC Threadlocker



### Description

#### PETEC threadlocker

##### medium strength, for connections till M36

For securing and sealing fine to coarse threaded connections such as screws, nuts, bolts and more. Removable with normal tool, also suitable for stainless steel and galvanized parts, resistant to corrosion, vibration, water, salt water, oil, fuel, coolant, hydrocarbon, and many other chemicals.

**Technical data:** color: blue, viscosity: 2000 to 7500 mPa·s, curing system: anaerobic, fixation time: 10 to 20 min., functional hardness: 1 to 3 hrs., shear resistance: 9 to 13 N/mm<sup>2</sup>, max. gap filling capability: 0,25mm, breakaway torque: 17 to 22 N/m, working temperature: +5°C to +35°C, temperature resistance: -55°C to +150°C, storage: 24 months, cool and dry place, **10g bottle**

|                  |                |
|------------------|----------------|
| Article number:  | 41412677       |
| Original number: | 91010          |
| EAN:             | 4019064754565  |
| EVP:             | <b>10.40 €</b> |

### Technical data

|                      |             |
|----------------------|-------------|
| Design               | adhesive    |
| Features             | medium-hard |
| Range of application | metal       |
| Main colour          | blue        |
| Container type       | bottle      |
| Amount               | 10.0 g      |
| Weight               | 0.010 kg    |