

Printing date: 25.04.2024 Version number 28 (replaces version 27) Revision date: 24.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Unterbodenschutz 1 Liter, schwarz
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

ad-AUTOTEILE-CARGO GmbH & Co. KG

Am Victoria-Turm 2 D-68163 Mannheim

E-mail: info@carat-gruppe.de

· Further information obtainable from:

Tel: +49(0)621-86080-0 Fax: +49(0)621-86080-390

· 1.4 Emergency telephone number:

Giftnotruf Berlin +49(0)30 30686 700 Advice in German and English.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3

H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

· Hazard statements

H225 Highly flammable liquid and vapour.

(Contd. on page 2)

Printing date: 25.04.2024 Version number 28 (replaces version 27) Revision date: 24.01.2024

Trade name: Unterbodenschutz - 1 Liter, schwarz

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P243 Take action to prevent static discharges.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with additions.

· Dangerous components:		
EC number: 920-750-0 Reg.nr.: 01-2119473851-33- 0001	Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066	25-<50%
EC number: 918-668-5	C9-aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	3-<5%
CAS: 108-32-7 EINECS: 203-572-1 Reg.nr.: 01-2119537232-48	Propylene carbonate © Eye Irrit. 2, H319	1-<3%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

- --

Printing date: 25.04.2024 Version number 28 (replaces version 27) Revision date: 24.01.2024

Trade name: Unterbodenschutz - 1 Liter, schwarz

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

Printing date: 25.04.2024 Version number 28 (replaces version 27) Revision date: 24.01.2024

Trade name: Unterbodenschutz - 1 Liter, schwarz

		(Contd. of page 3)
· DNELs		
Naphtha ((petroleum), hydrotreated light	
Oral	Long-term - systemic effects, general population	al 699 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, worker	773 mg/kg bw/day (Worker)
	Long-term - systemic effects, general population	al 699 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, worker	2.035 mg/m3 (Worker)
	Long-term - systemic effects, general population	al 608 mg/m3 (General Population)
PNECs		
CAS: 108-32-7 Propylene carbonate		
Aquatic compartment - freshwater 0,9		0,9 mg/L
Aquatic compartment - marine water 0,0		0,09 mg/L

0,81 mg/kg dw

7.400 mg/L

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls

Sewage treatment plant

Terrestrial compartment - soil

- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Aquatic compartment - water, intermittent releases 9 mg/L

Wash hands before breaks and at the end of work.

· Respiratory protection:



Filter A

· Hand protection

Not required.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material: ≥ 0,12 mm

· Penetration time of glove material

> 480 min.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

(Contd. on page 5)

Printing date: 25.04.2024 Version number 28 (replaces version 27) Revision date: 24.01.2024

Trade name: Unterbodenschutz - 1 Liter, schwarz

Body protection: Use protective suit.

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Black · Odour: Characteristic

· Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 106-140 ℃ (Naphtha (petroleum), hydrotreated light)

· Flammability Highly flammable. · Lower and upper explosion limit

· Lower: 0,9 Vol % (Naphtha (petroleum), hydrotreated light) 7 Vol % (Naphtha (petroleum), hydrotreated light) · Upper: · Flash point:

6 ℃ (DIN 53213, Naphtha (petroleum), hydrotreated

light)

· Auto-ignition temperature: >200 ℃ (Naphtha (petroleum), hydrotreated light)

 Decomposition temperature: Not determined.

· pH Mixture is non-soluble (in water).

· Viscosity:

· Kinematic viscosity At 40 ℃ >20.5 mm²/s · Dynamic At 20 ℃: 4.500 mPas

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

Not determined.

· Vapour pressure At 20 ℃: 20 hPa (Naphtha (petroleum), hydrotreated light)

· Vapour pressure At 50 ℃: 111 hPa

Internal Pressure:

· Vapour pressure At 50 ℃: 120 hPa

· Density and/or relative density

· Density At 20 ℃: 1,09 g/cm3 (DIN 51757) · Relative density Not determined.

Not determined. · Vapour density

· 9.2 Other information

35,29 % · VOC (EU): · VOC (EU): 384,6 g/l 31,18 % · VOCV:

· Appearance:

· Form: Fluid

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

35,3 % · Organic solvents: · Water: 0,0 %

· Solids content: 65,7 % (DIN 53216)

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

· Explosives Void

(Contd. on page 6)

Printing date: 25.04.2024 Version number 28 (replaces version 27) Revision date: 24.01.2024

Trade name: Unterbodenschutz - 1 Liter, schwarz

		(Contd. of page 5)
· Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
Flammable liquids	Highly flammable liquid and vapour.	
Flammable solids	Void	
 Self-reactive substances and mixtures 	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
 Self-heating substances and mixtures 	Void	
 Substances and mixtures, which emit 		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
 Desensitised explosives 	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
ATE (Acu	ATE (Acute Toxicity Estimates)	
Dermal	LD50	48.644-76.858 mg/kg
Naphtha (Naphtha (petroleum), hydrotreated light	
Oral	LD50	>5.000 mg/kg (RAT)
Dermal	LD50	>2.800 mg/kg (RABBIT)
Inhalative	LC 50	>23,3 mg/l (RAT)
C9-aroma	C9-aromatics	
Oral	LD50	5.558-7.093 mg/kg (rat)
Dermal	LD50	2.000-3.160 mg/kg (rabbit)
CAS: 108-	32-7 Propy	lene carbonate
Oral	LD50	33.520 mg/kg (RAT)
Dermal	LD50	>2.000 mg/kg (RABBIT)
Olein a a mu		>1.000 mg/l (CYPRINUS CARPIO)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date: 25.04.2024 Version number 28 (replaces version 27) Revision date: 24.01.2024

Trade name: Unterbodenschutz - 1 Liter, schwarz

(Contd. of page 6)

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information: No further relevant information available.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

Naphtha (petroleum), hydrotreated light

LL50/96 h >13,4 mg/l (SALMO GAIRDNERI / ONCORHYNCHUS MYKISS)

EL50/48 h 3 mg/l (DAPHNIA MAGNA)

EL50/72 h | 10-30 mg/l (SELENASTRUM CAPRICORNUTUM)

CAS: 108-32-7 Propylene carbonate

EC50/48 h >1.000 mg/l (DAPHNIA MAGNA)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of as dangerous waste.

•	•
· European	waste catalogue
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP14	Ecotoxic

(Contd. on page 8)

Printing date: 25.04.2024 Version number 28 (replaces version 27) Revision date: 24.01.2024

Trade name: Unterbodenschutz - 1 Liter, schwarz

(Contd. of page 7)

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR/RID/ADN, IMDG, IATA	UN1139
14.2 UN proper shipping nameADR/RID/ADN	1139 COATING SOLUTION, ENVIRONMENTALLY HAZARDOUS
· IMDG · IATA	COATING SOLUTION, MARINE POLLUTANT COATING SOLUTION
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class · Label	3 (F1) Flammable liquids.
· IMDG	
· Class	3 Flammable liquids.
· Label ·	3
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	II
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR/RID/ADN):	Symbol (fish and tree)
 14.6 Special precautions for user Hazard identification number (Kemler code) EMS Number: Stowage Category 	: 33 F-E, <u>S-E</u> В
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	Transport classification ADR/IMDG is based on packaging >450 ltr.
	(Contd. on page 9)

— El

Printing date: 25.04.2024 Version number 28 (replaces version 27) Revision date: 24.01.2024

Trade name: Unterbodenschutz - 1 Liter, schwarz

(Contd. of page 8)
Different classifications may apply for other packaging units.
Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN 1139 COATING SOLUTION, 3, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

· Hazard statements

H225 Highly flammable liquid and vapour. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P243 Take action to prevent static discharges.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 10)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date: 25.04.2024 Version number 28 (replaces version 27) Revision date: 24.01.2024

Trade name: Unterbodenschutz - 1 Liter, schwarz

(Contd. of page 9)

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	35,3

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Date of previous version: 12.07.2023
- · Version number of previous version: 27
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

(Contd. on page 11)

Page 11/11

Safety Data Sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date: 25.04.2024 Version number 28 (replaces version 27) Revision date: 24.01.2024

Trade name: Unterbodenschutz - 1 Liter, schwarz

(Contd. of page 10)

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

EII.