

Product data sheet

VICTORIA Electric trekking bike "Cysalo 9" (#2)



Description

Comfort e-bike for everyday use and leisure. The CYSALO 9 is the ideal comfort e-bike for anyone who wants to ride both in the city and off the beaten track. With its StVZO-compliant equipment and durable Schwalbe Energizer Plus Tour Tires, it offers safety and reliability. The practical MIK System Carrier makes it easy to attach bags, baskets or child seats and turns the bike into an affordable all-rounder.

Comfort and function

The 63 mm Suspension Fork guarantees comfortable rides even on uneven paths. The tilt-adjustable aluminum Stem and the 640 mm wide Handlebar ensure a relaxed riding position. The Gates CDC Straps in combination with the Shimano Nexus 8-speed hub gear offers a gear range of 244% and is particularly low-maintenance. You can choose between coaster brake or freewheel. The Shimano disc brakes at the front and rear ensure safe stops regardless of the weather.

Technical data

The CYSALO 9 is equipped with an Active Line Plus drive, which is operated via a Purion 200 Display. The high-quality 60 lux lighting from Herrmanns ensures visibility in the dark. The frame locks from Abus offer additional security when the bike is parked.

Target group

The CYSALO 9 is your everyday and leisure bike if you place particular value on comfort, durability and an excellent price-performance ratio. Discover the perfect blend of comfort and function for your daily adventures and enjoyable tours with the CYSALO 9.

Website



<https://www.victoria-bikes.com>

Article number: 02921036

Original number: 4251971179134

EAN: 4251971179134

EVP: 2999.00 €

Technical data

Battery capacity	545.0 Wh
Features	suspension fork, system carrier, chain guard, electronic sliding aid, fender
Colour designation	onyx grey
Main colour	grey
Travel	63 mm
Gender	gents
Gears	8-speed
Type	trekking bike
Wheel size	28 "
Material 1	aluminium
Engine power	250 W
Frame height	48 cm
Weight	28.200 kg
Stem length	90.0 mm
Permissible system weight	140 kg
Chainstay	510 mm
Toptube	601 mm
Wheel distance	1154 mm
Reach	390 mm
Seat tube	480 mm
Seat angle	74.0 °
Stack	645 mm
Steering tube	160 mm
Steering tube angle	70.0 °