

Product data sheet

CONTEC Aluminium Rim "Zen 26"



Description

The CONTEC Zen 26 aluminium rim forms the frame for a reliable Wheel that makes your daily commute by (e-)bike even smoother. It is suitable for 26" wheels with 32 spokes. Thanks to its hollow-chamber construction, the aluminum Zen Rim is suitable for a system weight of up to 150 kg. E-bikes can also be easily equipped with this rim. With an inner rim width of 21 mm, tires ranging in width from 35 to 62 mm fit on the rim.

Website



<https://www.contec-parts.com>

Article number: 03498182

Original number: WEB 21 26"

EAN: 4251971147812

EVP: 29.95 €

Technical data

Design	doublewall
Brake mounting	no mount, disc - Center Lock, disc - 5-hole, disc - 6-hole, roller brake, drum brake
Brake compatibility rim	universal
ETRTO	21-559
Main colour	black
For wheel	yes
Wheel size	26 "
Material 1	aluminium
Weight	0.594 kg
Text wheel configurator	suitable for E-bike
Valve type	Sclaverand (SV)
Wear indicator	yes
Permissible system weight	150 kg
Spoke Hole	no eyelets
Colour brake track	black
Hollow chamber shape	symmetrical
Rim height	21 mm
Rim inner width	21 mm
Rim outer width	28 mm
Spoke hole diameter	for 2.00 mm
Effective Rim Diameter	537 mm
max. spoke tension	1,200 Nm
Brake track	yes
Number of spoke holes	32 holes
Rim model	Zen 26