

Product data sheet

1979-74 EAN-No. 4000896**272853**



- Highly efficient light output of up to 500 lumens - Light range of up to 100 metres
- 3 levels of brightness: 20% / 50% / 100% (regulated via on/off switch)
- Extendable head for switching between flood and focus light
- Aluminium housing (black anodised) protects inner parts from the entrance of dust and splash water
- Pen clip
- Dual Power: can be operated with a 3.7 V - 750 mAh Li-ion rechargeable battery (included in the scope of delivery) or 2 AAA alkaline batteries LR03, 1.5 V (not included in the scope of delivery)
- Charging indicator: Red during the charging process, green when fully charged
- Dimensions (Ø x H): 18 x 158 mm
- Weight: 61 g (including 1x 3.7 V – 750 mAh Li-ion rechargeable battery)
- The on/off switch is easy to operate – even when wearing gloves
- Operating/storage conditions: -20° C to +60° C
- Power supply: Rechargeable battery or replaceable battery
- Number of batteries: 2 x 3.7 V 750 mAh lithium-ion rechargeable battery
- Power supply: USB cable (USB C)
- LED technology: XPG4
- Luminous flux 100%: 500 lm
- Operating time 100%: 2 h
- Range of light: 100 m
- Charging time: 3 h
- Type of protection (IP): IP44
- Protection rating (IK): IK08

Order Number

1979-74