

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2012

Revision: 16.10.2012

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** Continental Special Rim Cement Aluminium
- **Article number:** B1020001a
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation** Adhesives
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
CTA GmbH
Industriestr. 2
D-74321 Bietigheim-Bissingen
- **Further information obtainable from:**
fon: ++49-(0)-7142-506-0
fax: ++49-(0)-7142-506-140
e-mail: dirk.buchholz@cta-gmbh.de
- **Emergency telephone number:**
Giftnotruf Berlin: fon: ++49-(0)-30-30686 790 Beratung in Deutsch und Englisch

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.
Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07



GHS09

- **Signal word** Danger
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2012

Revision: 16.10.2012

Trade name: Continental Special Rim Cement Aluminium

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures
Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

| | | |
|--|---|--------|
| CAS: 110-82-7 EINECS: 203-806-2 Reg.nr.: 01-2119463273-41 | cyclohexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 | 25-50% |
| CAS: 64742-49-0 EC number: 921-024-6 Reg.nr.: 01-2119475514-35 | Naphtha (petroleum), hydrotreated light ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 | 25-50% |
| CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119565113-46-0000 | 2,6-di-tert-butyl-p-cresol ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302 | ≤ 2.5% |

Additional information: Remark P: concentration of benzene < 0,1 % (weight)

4 First aid measures

Description of first aid measures
After inhalation: In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

Information for doctor:
Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2012

Revision: 16.10.2012

Trade name: Continental Special Rim Cement Aluminium

(Contd. of page 2)

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2012

Revision: 16.10.2012

Trade name: Continental Special Rim Cement Aluminium

(Contd. of page 3)

· Control parameters
· Ingredients with limit values that require monitoring at the workplace:
110-82-7 cyclohexane

WEL Short-term value: 1050 mg/m³, 300 ppm
Long-term value: 350 mg/m³, 100 ppm

128-37-0 2,6-di-tert-butyl-p-cresol

WEL Long-term value: 10 mg/m³

· Additional information: The lists valid during the making were used as basis.

· Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:


Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties
· General Information
· Appearance:

| | |
|----------------|----------------|
| Form: | Fluid |
| Colour: | Beige |
| Odour: | Characteristic |

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2012

Revision: 16.10.2012

Trade name: Continental Special Rim Cement Aluminium

(Contd. of page 4)

| | |
|---|---|
| · Odour threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition Melting point/Melting range: Boiling point/Boiling range: | Undetermined. 80 °C |
| · Flash point: | -12 °C |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | 220 °C |
| · Decomposition temperature: | Not determined. |
| · Self-igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Explosion limits: Lower: Upper: | 0.9 Vol % 8.3 Vol % |
| · Vapour pressure at 20 °C: | 104 hPa |
| · Density at 20 °C: · Relative density · Vapour density · Evaporation rate | 0.81 g/cm ³ Not determined. Not determined. Not determined. |
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Segregation coefficient (n-octanol/water): | Not determined. |
| · Viscosity: Dynamic at 20 °C: Kinematic: | 5200 mPas Not determined. |
| · Solvent content: VOC (EC) | 70.5 % 70.50 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2012

Revision: 16.10.2012

Trade name: Continental Special Rim Cement Aluminium

(Contd. of page 5)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

110-82-7 cyclohexane

| | | |
|------|------|-------------------|
| Oral | LD50 | 12705 mg/kg (rat) |
|------|------|-------------------|

64742-49-0 Naphtha (petroleum), hydrotreated light

| | | |
|------|------|-------------------|
| Oral | LD50 | >5000 mg/kg (rat) |
|------|------|-------------------|

| | | |
|--------|------|----------------------|
| Dermal | LD50 | >2000 mg/kg (rabbit) |
|--------|------|----------------------|

128-37-0 2,6-di-tert-butyl-p-cresol

| | | |
|------|------|-----------------|
| Oral | LD50 | 890 mg/kg (rat) |
|------|------|-----------------|

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behaviour in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Very toxic for fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

| | |
|-----------|--|
| 08 04 09* | waste adhesives and sealants containing organic solvents or other dangerous substances |
|-----------|--|

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2012






Revision: 16.10.2012

Trade name: Continental Special Rim Cement Aluminium

(Contd. of page 6)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

| | |
|---|---|
| · UN-Number | UN1133 |
| · ADR, IMDG, IATA | |
| · UN proper shipping name | 1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS, special provision 640H |
| · ADR | ADHESIVES (CYCLOHEXANE, Naphtha (petroleum), hydrotreated light) |
| · IMDG | ADHESIVES |
| · IATA | |
| · Transport hazard class(es) | |
| · ADR | |
|  |  |
| · Class | 3 (F1) Flammable liquids. |
| · Label | 3 |
| · IMDG | |
|  |  |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| · IATA | |
|  | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| · Packing group | III |
| · ADR, IMDG, IATA | |
| · Environmental hazards: | Product contains environmentally hazardous substances: cyclohexane, Naphtha (petroleum), hydrotreated light |
| · Marine pollutant: | Yes |
| · Special marking (ADR): | Symbol (fish and tree) |
| · Special precautions for user | Warning: Flammable liquids. |
| · Danger code (Kemler): | 33 |
| · EMS Number: | F-E,S-D |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2012

Revision: 16.10.2012

Trade name: Continental Special Rim Cement Aluminium

(Contd. of page 7)

| | |
|--|--|
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Tunnel restriction code | D/E |
| · UN "Model Regulation": | UN1133, ADHESIVES, special provision 640H, ENVIRONMENTALLY HAZARDOUS, 3, III |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02 GHS07 GHS09

- **Signal word** Danger
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P321 Specific treatment (see on this label).
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2012

Revision: 16.10.2012

Trade name: Continental Special Rim Cement Aluminium

(Contd. of page 8)

*H400 Very toxic to aquatic life.**H410 Very toxic to aquatic life with long lasting effects.**H411 Toxic to aquatic life with long lasting effects.***· Department issuing MSDS:** Abteilung Produktsicherheit**· Contact:** Dr. Dirk Buchholz**· Abbreviations and acronyms:***RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)**ICAO: International Civil Aviation Organization**ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonized System of Classification and Labelling of Chemicals**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent*

GB