Product data sheet

TEROSON Sealant "RB 53"



Article number:	41438136
Original number:	2955106
EAN:	2014143813067
EVP:	**48.55 €**

Technical data

Design	seal / repair material
Features	pasty, coatable and fillable, aging / weather resistant, overpainted
Range of application	metal, plastic
Main colour	green
Container type	can
Amount	1000.0 g
Weight	1.000 kg
Temperature range up to	80 °C
Temperature range from	-25 °C

Description

TEROSON "RB 53" Sealant
Terolan 53 Special, solvent-based, brush-applicable sealant based on SBR (styrene-butadiene rubber)
Sealing for seams, particularly lap seams, on front and rear bumpers, the floor assembly in the passenger compartment, the side panels, or the wheel wells. Tolerates light soiling, adheres well to bare, galvanized, primed, and painted sheet steel as well as to rigid PVC, and can be easily painted over with all commercially available automotive paints (solvent- and water-based) once it is completely dry. It is essential that the sealant bead is completely dry before painting. Skin formation time: approx. 3–5 min.; full cure time: 20–48 h; film thickness: 3 mm. The included brushes can be used to replicate factory brush textures., **1-kg can**

This product data sheet is based on the information available at the time of generation. Subsequent changes to prices, technical specifications, or product information are possible. The current details provided with the item are authoritative.

Date of generation: 05.10.2026