

SONAX Paint sealer set "CeramicCoating CC Evo"



Article number: 40262149

Original number: 02378410

EAN: 4064700237841

EVP: 171.25 €

Technical data

Application	paint
Design	paint sealing
Features	ready-to-use
Range of application	paint care
Main colour	black
Secondary colour	gold
Container type	carton
Assortment	8 pieces

Description

SONAX Paint Sealing Set "CeramicCoating CC Evo" PROFILINE, paint protection for up to 5 years

For a professional two-component coating of paintwork. The set contains the two sealing products SONAX PROFILINE CeramicCoating CC Evo BaseCoat and SONAX PROFILINE CeramicCoating CC EvoGlossCoat in the latest formula generation, as well as four applicators. Thanks to the new formulations, durability has been improved even further without compromising on processing. Premium coating with the best resistance and outstanding visual and tactile properties.

Application:

Ensure good ventilation during application. Application temperature from +10° C. Optimum application temperature 20 to 30° C. Caution with refinishing: Check paint fastness beforehand. After polishing the paint, spray SONAX PREPARE (#02373000) as a basic cleaner into a soft touch microfiber cloth, wipe the paint with it and prepare it for coating. CC Evo is then applied in two stages. In the first sealing step, BASECOAT Evo is applied thinly to partial areas using an applicator sponge. After a short flash-off time, the excess product is wiped off with a Coating Towel (#0451100), then a new partial surface is treated. After a waiting time of 1 hour, GLOSSCOAT Evo is applied thinly with a new applicator sponge in a second step. The flash-off time here should be between 3 and 5 minutes. Then remove the excess product with a SONAX Coating Towel (#04511000). If the product begins to harden in the sponge on large vehicles, a new application sponge should be used. The fully treated vehicle must be left to dry for at least 4 hours and must not get wet during this time. Ideally, the vehicle should be left in a room overnight. Do not apply to hot surfaces and do not allow to dry. The first vehicle wash should be carried out after 1 week at the earliest. Important: Do not use highly alkaline cleaners, as these can attack the protective coating., **in box**, contents 8 pcs.