

# Product data sheet



## brennenstuhl Work light "SL 2500 AT"



### Description

**BRENNENSTUHL "SL 2500 AT" Work Light**  
**Li-ion battery (2x), LED, 24 W, 2500 lm, automatic legs on stand, IP65**  
This construction floodlight with stand features three light panels that can be adjusted horizontally by 360° and vertically by 180°, enabling full-area illumination. The brightness can be flexibly adjusted via three brightness levels (100% / 50% / 30%), achieving a maximum light output of 2,500 lm. For optimal lighting ambiance, three selectable color temperatures—3,000 K, 4,000 K, and 5,000 K—are also available, allowing for customizable lighting ranging from warm white to neutral white. Thanks to the built-in memory function, the last selected setting is automatically saved. The light head can be used flexibly with or without a stand and is suitable both as a stand-mounted floodlight with a height of up to 1.30 m and as a portable construction floodlight. For added safety, the light automatically turns off as soon as all panels are closed.

**Technical Specifications:**  
Voltage: 3.7 V  
Light type: Tripod spotlight  
Housing Material: Metal  
Luminous flux: 2,500 lm  
Protection class: III  
Protection rating: IP65  
Impact resistance: IK07  
Color temperature: 3,000 K, 4,000 K, 5,000 K  
Height: 130 cm  
Weight: 2.45 kg  
Charging time: 6 hours, **includes Transport Bag**

|                  |               |
|------------------|---------------|
| Article number:  | 89660497      |
| Original number: | 1173700026    |
| EAN:             | 4007123700936 |
| EVP:             | 141.65 €      |

| Technical data           |                                                                                                           |
|--------------------------|-----------------------------------------------------------------------------------------------------------|
| Design                   | work light                                                                                                |
| Battery type             | Li-Ion                                                                                                    |
| Features                 | 360° illumination, foldable, with holder, with a tripod, pivoted, splash-proof, dustproof, USB connection |
| Range of application     | Leisure, Workshop                                                                                         |
| Main colour              | black                                                                                                     |
| Secondary colour         | grey                                                                                                      |
| Colour temperature up to | 5000 K                                                                                                    |
| Colour temperature from  | 3000 K                                                                                                    |
| Intensity                | 2500 lumen                                                                                                |
| Height                   | 130.0 cm                                                                                                  |
| Capacity                 | 4000 mAh                                                                                                  |
| Power                    | 24.0 W                                                                                                    |
| Operating time max.      | 15 h                                                                                                      |
| Illuminant               | LED                                                                                                       |
| Light mode               | 100%, 30%, 50%                                                                                            |
| Light colour             | neutral white                                                                                             |
| Material                 | aluminium                                                                                                 |
| Material 2               | plastic                                                                                                   |
| Protection class         | III                                                                                                       |
| Voltage                  | 3.7 V                                                                                                     |
| Power supply             | battery mode                                                                                              |

# Product data sheet



## brennenstuhl Work light "SL 2500 AT"

