

Product data sheet

1979-75

EAN-No. 4000896272891



Application:

UV light for faster and clearer localisation of leaks

- Highly efficient light output of up to **800 lumens** - Light range of up to 150 metres
- Swivelling head (90°) for different light angles
- 2 brightness levels: 50%/100%/ UV (long button press for UV light)
- Aluminium housing (black anodised) stops dust and splash water entering the internal parts (IP44)
- 2-in-1 button for charging and status display:
Charging display:
 - Solid green (fully charged)
 - Flashing green (charging)Status display:
 - Solid blue (battery capacity OK)
 - Flashing blue (approx. 10% battery capacity)
- High-quality pen clip
- Strong holding magnet
- Dimensions (∅ x H): 30.5 x 146 mm
- Weight: 165 g (including 1* 3.7 V – 2600 mAh Li-ion rechargeable battery)
- The on/off switch is easy to operate – even when wearing gloves
- Rotatable charging port cover
- Operating/storage conditions: -20° C to +60° C
- Number of batteries: 1 x 3.7 V 2600 mAh Lithium-ion rechargeable battery
- Power supply: USB cable (USB C)
- LED technology: 395 nm UV, XPG4
- Luminous flux 100%: 800 lm
- Operating time 100%: 3 h
- Range of light: 150 m
- Charging time: 5 h
- Type of protection (IP): IP44
- Protection rating (IK): IK08

Order Number

1979-75