

CONTEC Aluminium Rim "Classic Z19"



Description

CONTEC "Classic Z19" Aluminium Rim
28" x 1.75, 19-622, max. load up to 150 kg system weight
Aluminum, hollow-wall construction, side-turned
double-eyelet, DV, 21.5 mm high, 19 mm inner width, 24 mm outer width,
maximum spoke tension 1200 N, suitable for e-bikes, with wear indicator, **32**
holes, silver anodized

Website



<https://www.contec-parts.com>

Article number:	03498169
Original number:	9362202321255852
EAN:	4251507941518
EVP:	34.95 €

Technical data

Design	doublewall
Brake mounting	no mount, disc - Center Lock, disc - 5-hole, disc - 6-hole, roller brake, drum brake
Brake compatibility rim	universal
ETRTO	19-622
Main colour	silver
For wheel	yes
Wheel size	28 / 29 "
Material 1	aluminium
Weight	0.724 kg
Valve type	Dunlop (DV), Schrader (AV)
Wear indicator	yes
Permissible system weight	150 kg
Spoke Hole	double eyelets
Colour brake track	silver
Hollow chamber shape	symmetrical
Rim height	22 mm
Rim inner width	19 mm
Rim outer width	24 mm
Spoke hole diameter	for 2.00 mm
Eyelet color	silver
max. spoke tension	1,200 N
Brake track	yes
Number of spoke holes	32 holes
Rim model	Classic Z19

CONTEC Aluminium Rim "Classic Z19"

