Product data sheet

BS-BATTERY Battery "BTX4L-BS"



Article number:	05378054
Original number:	300889
EAN:	3564093008895
EVP:	**28.51 €**

Technical data

Design	MTF, with acid pack
Width	70.0 mm
Range of application	motorcycle
Energy	51.20 Wh
Bleeding	internal
Filling quantity	0.2 l
Height	85.0 mm
Cold start current CCA	55 A
Capacity 10 Hr	5.0 Ah
Capacity 20 Hr	4.2 Ah
Length	113.0 mm
Minus pole	front left
Plus pole	front right
Weight	1.550 kg
Voltage	12V
Screwing	M5

Description

BS-BATTERY Battery "BTX4L-BS"
ETN: 503 014 003

DIN: 50314, **MTF**maintenance-free, **5 Ah**

Attach the supplied acid pack after removing the adhesive strip and allow it to run evenly into all cells. Leave to stand for about 1-2 hours and then press the sealing strip on firmly. Once filled, the battery is sealed and no further maintenance is necessary.
CautionBatteries from 12 V may require recharging! Never open or drill into these sealed (MTF) batteries or remove the sealing strip!

This product data sheet is based on the information available at the time of generation. Subsequent changes to prices, technical specifications, or product information are possible. The current details provided with the item are authoritative.

Date of generation: 28.10.2026