Product data sheet

innobike Chain Spray "106 Kettenfluid"



Article number:	03561909
Original number:	IC-106300
EAN:	4260097140195
EVP:	**16.80 €**

Technical data

Range of application	bike
Main colour	white
Secondary colour	orange
Accent colour	white
Container type	spray can
Content	0.3 l
Type	lubricant, cleaning
Material	sheet metal
Material 2	plastic
Weight	0.291 kg

Description

Developed for long-lasting lubrication
Behind the properties of the product is a carefully created formula consisting of several components.
Ester-based organic solvents with a high dissolving capacity ensure cleaning and rust removal. The solvents also ensure penetration into the tightest of fits.
Gradual evaporation of the solvent components results in a dry, non-sticky lubricating film that nevertheless adheres firmly to the surface. Due to the good adhesion, the lubricating film does not spin off, which means a long service life for the lubrication and enables lubrication intervals to be extended considerably.
The lubricating film made of specially developed polymers can also withstand high mechanical loads and the non-stick properties prevent dust and dirt from being deposited on the surface. Of course, the tightly closed, very well adhering lubricating film also provides very good corrosion protection.

Application instructions

- Application interval: 150 - 300 km, depending on the terrain and weather conditions.
- Apply after driving. Allow a reaction time of 4-6 hours. 105 High Tech KETTENFLUID works overnight.
- Avoid spray mist by using the brushes.
- Avoid contacts with brakes of any kind; loss of braking power possible.
- 105 High Tech KETTENFLUID infiltrates wetness so that the chains can be used immediately after the bike wash.

Application

- Apply 105 High Tech KETTENFLUID with Brush Attachment to the rear small Sprocket.
- Turn the pedals backwards in freewheel mode and spray continuously until 105 High Tech KETTENFLUID drips from the large bottom bracket sprocket.
- Leave to work for 46 hours. During this time, the Cleaner contained in the fluid evaporates and a thin, non-slip lubricating film remains on the Chain.
- Application with the capillary tube is ideal for all types of cables, bearings and other moving parts. Removes gumming and dirt. Immediately eliminates stiffness.

This product data sheet is based on the information available at the time of generation. Subsequent changes to prices, technical specifications, or product information are possible. The current details provided with the item are authoritative.

Date of generation: 14.10.2026