Product data sheet

VICTORIA Electric trekking bike "Manoc 6" (#1)



Website

https://www.victoria-bikes.com

Article number:	02920255
Original number:	BK25HV0522
EAN:	4251971150898
EVP:	**4699.00 €**

Description

The top derailleur model in the MANOC premium trekking series is the ideal partner for long-distance touring.

The smart Bosch system delivers the maximum of what is currently possible with the "Performance CX" drives and the highest-capacity "PowerTube 750" Battery. Additional information that the "Kiox 300" color display does not provide can be transmitted to your smartphone via the eFlow Bike app. Other apps, such as Komoot or Strava, then use the information for navigation and route planning.

With its 80 mm of travel, the air-sprung Fork offers plenty of comfort and absorbs any bumps in the road from the wide, low rolling resistance tires.

The eleven gears come from a Shimano "Deore XT" rear derailleurs. This, as well as the chain and cassette, come from the Linkglide series and are around three times more wear-resistant and comfortable than a comparable standard Hyperglide version.

As with all new Victoria developments, the batteries integrated in the down tube can be removed from the top, making it unnecessary to remove them from the bottom. However, in view of the large capacities and the associated battery weight, we recommend charging at the MANOC instead, as it is simply more convenient.

With a permissible total weight of 170 kg, the MANOC 6 is the ideal touring companion and, thanks to the MIK luggage carrier system, can firmly attach panniers and the like without them slipping during the ride.

,

Technical data

Battery capacity	750.0 Wh
Features	suspension fork, frame lock, chain guard, electronic sliding aid, fender
Colour designation	galaxy white
Main colour	silver
Secondary colour	black
Travel	80 mm
Gender	gents
Gears	11-speed
Type	trekking bike
Wheel size	28 "
Material 1	aluminium
Engine power	250 W
Frame height	58 cm
Weight	28.800 kg
Permissible system weight	170 kg
Chainstay	483 mm
Toptube	660 mm
Wheel distance	1214 mm
Reach	457 mm
Seat tube	580 mm
Seat angle	72.0 °
Stack	671 mm
Steering tube	180 mm
Steering tube angle	69.0 °