Product data sheet

LOCTITE Threadlocker "2701"



Article number:	41415167
Original number:	29686
EAN:	4100630296869
EVP:	**10.65 €**

Technical data

Design	adhesive
Features	high-strength
Range of application	metal
Main colour	green
Container type	bottle
Content	5 ml
Weight	0.005 kg

Description

LOCTITE Screw Retention "2701"
High-strength, low-viscosity, green, methacrylate-based Screw Retention
Prevents unwanted movement, self-loosening, leaks, and corrosion in the thread, and is vibration-resistant. Through-threads are sealed at the same time. Particularly suitable for chrome-plated surfaces. Tolerates minor contamination from industrial oils. For all metal threaded connections. Fluoresces under UV light.

Technical Data: Breakaway torque for M10 screws: 38 Nm, hand-tightening time on steel: 10 min, hand-tightening time on brass: 4 min, hand-tightening time on stainless steel: 25 min, operating temperature range: -55 °C to +150 °C, disassembly: Heat the nut or screw locally to approx. 250 °C and disassemble while still hot., **5 ml water bottle, self-service packaging**

This product data sheet is based on the information available at the time of generation. Subsequent changes to prices, technical specifications, or product information are possible. The current details provided with the item are authoritative.

Date of generation: 13.11.2026