according to Regulation (EC) No. 1907/2006 (REACH)

Version number: GHS 3.0 Revision: 2024-02-26 Replaces version of: 2024-02-22 (GHS 2)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product identifier** 

1.4

Trade name COREXX Keramik-Spray - 400 ml

Unique formula identifier (UFI) 6T19-29K3-2Q3N-0YWW

Article number 40008344

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses General use Lubricant

1.3 Details of the supplier of the safety data sheet

> ad-AUTOTEILE-CARGO Gmbh & Co. KG Am Victoria-Turm 2 68163 Mannheim Germany

Telephone: +49 (0)621 / 8 60 80 - 0 e-mail: info@carat-gruppe.de Website: www.corexx.eu **Emergency telephone number** 

**Emergency information service** 

+49 (0)621 / 8 60 80 - 0 (über die Zentrale vermittelt) This number is only available during the following office hours: Mon-Fri 08:00 - 17:00

#### **SECTION 2: Hazards identification**

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
2.3	aerosols	1	Aerosol 1	H222,H229
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

2.2 **Label elements** 

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word danger

**Pictograms** 

GHS02, GHS07



### **Hazard statements**

Extremely flammable aerosol. H222

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

If medical advice is needed, have product container or label at hand. Keep out of reach of children. P101

P102

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P410+P412

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous ingredients for labelling Naphtha (petroleum), hydrotreated light, propan-2-ol

Germany: en Page: 1 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

### 40008344 - COREXX Keramik-Spray - 400 ml

Version number: GHS 3.0 Replaces version of: 2024-02-22 (GHS 2) Revision: 2024-02-26

#### Other hazards

#### Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq$  0,1%.

#### **Endocrine disrupting properties**

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0.1\%$ .

# **SECTION 3: Composition/information on ingredients**

#### **Substances**

Not relevant (mixture)

#### 3.2 **Mixtures**

#### **Description of the mixture**

Identifier	Name of substance	Wt%	Classification acc. to GHS	Pictograms	Notes	Specific Conc. Limits
CAS No 106-97-8	butane	25 - < 50	Flam. Gas 1B / H221 Press. Gas C / H280		C GHS-HC	
EC No 203-448-7					U(b)	
Index No 601-004-00-0						
REACH Reg. No 01- 2119474691- 32-xxxx						
CAS No 74-98-6	propane	10-<25	Flam. Gas 1A / H220 Press. Gas L / H280		GHS-HC U(c)	
EC No 200-827-9						
Index No 601-003-00-5						
REACH Reg. No 01- 2119486944- 21						
CAS No 64742-49-0	Naphtha (petro- leum), hydro- treated light	10-<25	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336	<b>⟨₺⟩⟨!⟩</b>	P(b)	
EC No 265-151-9	treated light		Asp. Tox. 1 / H304 Aquatic Chronic 2 /	<b>1</b>		
Index No 649-328-00-1			H411 	Was A		
CAS No 67-63-0	propan-2-ol	1-<5	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319	<b>⟨₺⟩⟨!⟩</b>	GHS-HC	
EC No 200-661-7			STOT SE 3 / H336			
Index No 603-117-00-0						
REACH Reg. No 01- 2119457558- 25 01- 2119457558- 25-xxxx						

Notes

Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers. Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI) C: GHS-HC:

Germany: en Page: 2 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

#### 40008344 - COREXX Keramik-Spray - 400 ml

Version number: GHS 3.0 Revision: 2024-02-26

Replaces version of: 2024-02-22 (GHS 2)

Notes

P(b): The classification as a carcinogen or mutagen is not required. The substance contains less than 0,1 % w/w benzene

(EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply
The allocation to the group 'compressed gas' is based on the physical state in which the gas is packaged
The allocation to the group 'liquefied gas' is based on the physical state in which the gas is packaged U(b):

U(c):

#### Remarks

For full text of abbreviations: see SECTION 16.

#### **SECTION 4: First aid measures**

#### Description of first aid measures

#### **General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eve contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

#### 4.3 Indication of any immediate medical attention and special treatment needed

### SECTION 5: Firefighting measures

### Extinguishing media

# Suitable extinguishing media

Water spray, BC-powder

# Unsuitable extinguishing media

#### Special hazards arising from the substance or mixture 5.2

#### **Hazardous combustion products**

Carbon monoxide (CO), Carbon dioxide (CO2)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

### **SECTION 6: Accidental release measures**

## Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Remove persons to safety.

#### For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

#### 6.2 **Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

#### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

Germany: en Page: 3 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

#### 40008344 - COREXX Keramik-Spray - 400 ml

Version number: GHS 3.0 Revision: 2024-02-26 Replaces version of: 2024-02-22 (GHS 2)

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

# **SECTION 7: Handling and storage**

Reference to other sections

#### Precautions for safe handling

#### Recommendations

#### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### Conditions for safe storage, including any incompatibilities 7.2

#### Managing of associated risks

#### Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

#### **Packaging compatibilities**

Keep only in original container.

#### Storage class (LGK) TRGS 510

LGK 2 B (aerosol dispensers and lighters)

#### 7.3 Specific end use(s)

See section 16 for a general overview.

# SECTION 8: Exposure controls/personal protection

#### **Control parameters**

Occup	Occupational exposure limit values (Workplace Exposure Limits)										
Coun- try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceiling- C [ppm]	Ceiling- C [mg/ m³]	Nota- tion	Source
DE	butane	106-97-8	AGW	1,000	2,400	4,000	9,600				TRGS 900
DE	propan-2-ol	67-63-0	AGW	200	500	400	1,000			Υ	TRGS 900
DE	propane	74-98-6	AGW	1,000	1,800	4,000	7,200				TRGS 900

Notation

Ceiling-C

ceiling value is a limit value above which exposure should not occur short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period (unless otherwise specified)

**TWA** time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

hours time-weighted average (unless otherwise specified) a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the biological limit value (BGW) are adhered to

Biological limit values							
Country	Name of agent	Parameter	Notation	Identifier	Value	Source	
DE	2-propanol	acetone		BLV	25 mg/l	TRGS 903	
DE	2-propanol	acetone		BLV	25 mg/l	TRGS 903	

Germany: en Page: 4 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

#### 40008344 - COREXX Keramik-Spray - 400 ml

Version number: GHS 3.0 Revision: 2024-02-26 Replaces version of: 2024-02-22 (GHS 2)

## **Relevant DNELs of components**

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Naphtha (petro- leum), hydro- treated light	64742-49-0	DNEL	5,306 mg/ m <sup>3</sup>	human, inhalat- ory	worker (industry)	chronic - systemic effects
Naphtha (petro- leum), hydro- treated light	64742-49-0	DNEL	13,964 mg/ kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
propan-2-ol	67-63-0	DNEL	1,723 mg/ m <sup>3</sup>	human, inhalat- ory	worker (industry)	acute - systemic effects
propan-2-ol	67-63-0	DNEL	500 mg/m <sup>3</sup>	human, inhalat- ory	worker (industry)	chronic - systemic effects
propan-2-ol	67-63-0	DNEL	888 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

#### **Relevant PNECs of components**

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
propan-2-ol	67-63-0	PNEC	160 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	water	short-term (single instance)
propan-2-ol	67-63-0	PNEC	140.9 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	water	intermittent re- lease
propan-2-ol	67-63-0	PNEC	140.9 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	freshwater	short-term (single instance)
propan-2-ol	67-63-0	PNEC	140.9 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	marine water	short-term (single instance)
propan-2-ol	67-63-0	PNEC	2,251 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
propan-2-ol	67-63-0	PNEC	552 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
propan-2-ol	67-63-0	PNEC	552 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	marine sediment	short-term (single instance)
propan-2-ol	67-63-0	PNEC	28 <sup>mg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single instance)

## 8.2 Exposure controls

# Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)







Personal protective equipment shall be used when the risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

#### **Eye/face protection**

Use protective eyewear to guard against splash of liquids.

Skin protection Hand protection

Wear protective gloves. (Splash protection)

Type of material

NR: natural rubber, latex, FKM: fluoro-elastomer

Breakthrough times of the glove material

>480 minutes (permeation: level 6)

Germany: en Page: 5 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

#### 40008344 - COREXX Keramik-Spray - 400 ml

Version number: GHS 3.0 Replaces version of: 2024-02-22 (GHS 2) Revision: 2024-02-26

#### Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

# **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.
Full face mask/half mask/quarter mask (EN 136/140).
Type: AX-P2 (gas filters and combined filters against low-boiling point organic compounds and particles, colour code: Brown/ White).

#### **Environmental exposure controls**

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

# SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	aerosol (spray aerosol)			
Colour	white			
Odour	characteristic			
Melting point/freezing point	not determined			
Boiling point or initial boiling point and boiling range	-161.5 °C at 1,013 hPa			
Flammability	flammable aerosol in accordance with GHS criteria			
Lower and upper explosion limit	50 g/m³ - 335 g/m³ / 1 vol% - 15 vol%			
Flash point	-87 °C at 1,013 hPa			
Auto-ignition temperature	264 °C (auto-ignition temperature (liquids and gases))			
Decomposition temperature	not relevant			
pH (value)	not determined			
Kinematic viscosity	not relevant			
Solubility(ies)	not determined			

## **Partition coefficient**

Partition coefficient n-octanol/ water (log value)	this information is not available

Vapour pressure	4,200 hPa at 20 °C

# Density and/or relative density

Density	0.7053 <sup>g</sup> / <sub>ml</sub> (calculated value)
Relative vapour density	information on this property is not available

#### 9.2 Other information

Information with regard to physical hazard classes	there is no additional information
Other safety characteristics	
Temperature class (EU, acc. to ATEX)	T3 (maximum permissible surface temperature on the equipment: 200°C)

Page: 6 / 12 Germany: en

according to Regulation (EC) No. 1907/2006 (REACH)

#### 40008344 - COREXX Keramik-Spray - 400 ml

Version number: GHS 3.0 Revision: 2024-02-26 Replaces version of: 2024-02-22 (GHS 2)

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

#### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

#### Hints to prevent fire or explosion

Protect from sunlight.

#### 10.5 Incompatible materials

Oxidisers

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification according to GHS (1272/2008/EC, CLP)

#### **Acute toxicity**

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if inhaled.

## Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

## Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

## **Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

#### 11.2 Information on other hazards

There is no additional information.

Germany: en Page: 7 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

#### 40008344 - COREXX Keramik-Spray - 400 ml

Version number: GHS 3.0 Revision: 2024-02-26 Replaces version of: 2024-02-22 (GHS 2)

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects. Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)

#### Aquatic toxicity (chronic) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
propan-2-ol	67-63-0	LC50	>10,000 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	24 h

# 12.2 Persistence and degradability

#### **Biodegradation**

The relevant substances of the mixture are readily biodegradable.

## **Degradability of components**

Name of sub- stance	CAS No	Process	Degradation rate	Time	Method	Source
Naphtha (pet- roleum), hy- drotreated light	64742-49-0	oxygen deple- tion	83 %	10 d		ECHA
propan-2-ol	67-63-0	oxygen deple- tion	53 %	5 d		ECHA

#### 12.3 Bioaccumulative potential

Data are not available.

# **Bioaccumulative potential of components**

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butane	106-97-8		1.09 (pH value: 7, 20 °C)	
propane	74-98-6		1.09 (pH value: 7, 20 °C)	
Naphtha (petroleum), hydro- treated light	64742-49-0	501.2	3.6 (pH value: 7, 20 °C)	
propan-2-ol	67-63-0		0.2 (pH value: 7, 25 °C)	

#### 12.4 Mobility in soil

Data are not available.

# 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .

## 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq$  0,1%.

## 12.7 Other adverse effects

Data are not available.

Germany: en Page: 8 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

#### 40008344 - COREXX Keramik-Spray - 400 ml

Version number: GHS 3.0 Revision: 2024-02-26 Replaces version of: 2024-02-22 (GHS 2)

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

#### List of wastes, (Recommendations)

#### **Product**

07 06 04\* Other organic solvents, washing liquids and mother liquors

#### **Product residues**

16 05 04\* Gases in pressure containers (including halons) containing hazardous substances

07 06 04\* Other organic solvents, washing liquids and mother liquors

#### **Packagings**

15 01 04 Metallic packaging

#### **Remarks**

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR/RID/ADN UN 1950
IMDG-Code UN 1950
ICAO-TI UN 1950

14.2 UN proper shipping name

ADR/RID/ADN AEROSOLS IMDG-Code AEROSOLS

ICAO-TI Aerosols, flammable

14.3 Transport hazard class(es)

 ADR/RID/ADN
 2 (2.1)

 IMDG-Code
 2.1

 ICAO-TI
 2.1

**14.4** Packing group not assigned

**14.5 Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations

# 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

# 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

# Information for each of the UN Model Regulations

#### Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) Additional information

Classification code 5F Danger label(s) 2.1



Special provisions (SP) 190, 327, 344, 625

Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D

Germany: en Page: 9 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

#### 40008344 - COREXX Keramik-Spray - 400 ml

Version number: GHS 3.0 Revision: 2024-02-26 Replaces version of: 2024-02-22 (GHS 2)

International Maritime Dangerous Goods Code (IMDG) Additional information

Marine pollutant - Danger label(s) 2.1

2

Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U

International Civil Aviation Organization (ICAO-IATA/DGR) Additional information

Danger label(s) 2.1

Stowage category

Special provisions (SP) A145, A167 Excepted quantities (EQ) E0 Limited quantities (LQ) 30 kg

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

none of the ingredients are listed

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

National regulations (Germany)

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling

substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK (water 2 obviously hazardous to water

hazard class)

Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentra- tion	Notation
5.2.5	organic substances		≥ 25 wt%	0.5 <sup>kg</sup> / <sub>h</sub>	50 <sup>mg</sup> / <sub>m³</sub>	3)

#### Notation

3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

#### **National inventories**

Country	Inventory	Status
EU	REACH Reg.	all ingredients are listed

Legend

REACH Reg. REACH registered substances

## 15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

Germany: en Page: 10 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

#### 40008344 - COREXX Keramik-Spray - 400 ml

Version number: GHS 3.0 Revision: 2024-02-26 Replaces version of: 2024-02-22 (GHS 2)

### **SECTION 16: Other information**

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
1.3	Details of the supplier of the safety data sheet: ad-AUTOTEILE-CARGO Gmbh & Co. KG Am Victoria-Turm 2 68163 Mannheim Germany	Details of the supplier of the safety data sheet: ad-AUTOTEILE-CARGO Gmbh & Co. KG Am Victoria-Turm 2 68163 Mannheim Germany	yes
	Telephone: +49 (0)621 / 8 60 80 - 0 Website: www.corexx.eu	Telephone: +49 (0)621 / 8 60 80 - 0 e-mail: info@carat-gruppe.de Website: www.corexx.eu	
1.4	Emergency information service: +49 (0)621 / 8 60 80 - 0 (über die Zentrale ver- mittelt) This number is only available during the follow- ing office hours: Mon-Fri 09:00 - 17:00	Emergency information service: +49 (0)621 / 8 60 80 - 0 (über die Zentrale ver- mittelt) This number is only available during the follow- ing office hours: Mon-Fri 08:00 - 17:00	yes

#### Abbreviations and acronyms

Descriptions of used abbreviations. Abbr.

ADN.

Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).

Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Danger-ADR.

Accord europeen relatif au transport international car marchandises dangereuses par voies de navigation interieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).

Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN).

Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN).

Workplace exposure limit.

Hazardous to the aquatic environment - chronic hazard.

Aspiration hazard.

Bioconcentration factor.

Biochemical Oxygen Demand.

Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).

Celling value.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Chemical oxygen demand.

Dangerous Goods Regulations (see IATA/DGR).

Derived No-Effect Level.

The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).

Floretoric disruptor.

European Inventory of Existing Commercial Chemical Substances.

European In ADR/RID/ADN.
AGW.
Aquatic Chronic.
Asp. Tox.
BCF.
BOD.
CAS.
Ceiling-C.
CLP.
COD.
DGR.
DNEL.
EC No.

ED. EINECS. ELINCS. EMS. Eye Dam. Eye Irrit. Flam. Gas. Flam. Liq. GHS. ICAO. ICAO. ICAO. ICAO. II. IMDG. IMDG. IMDG-Code. Index No. LC50.

LGK. Log KOW. NLP. PBT. PNEC. Ppm. Press. Gas. REACH. RID.

Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval.

Lagerklasse (storage class according to TRGS 510, Germany).

n-Octanol/water.

No-Longer Polymer.

Persistent, Bioaccumulative and Toxic.

Predicted No-Effect Concentration.

Parts per million.

Gas under pressure.

Registration, Evaluation, Authorisation and Restriction of Chemicals.

Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).

Corrosive to skin.

Irritant to skin.

Irritant to skin.

Short-term exposure limit.

Specific target organ toxicity - single exposure.

Substance of Very High Concern.

Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany).

Arbeitsplatzgrenzwerte (TRGS 900).

Biologische Grenzwerte (TRGS 903).

Time-weighted average.

Very Persistent and very Bioaccumulative.

Skin Corr. Skin Irrit. STEL. STOT SE. SVHC. TRGS. TRGS 900. TRGS 903. VPvB.

#### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Germany: en Page: 11 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

### 40008344 - COREXX Keramik-Spray - 400 ml

Version number: GHS 3.0 Revision: 2024-02-26 Replaces version of: 2024-02-22 (GHS 2)

# List of relevant phrases (code and full text as stated in section 2 and 3)

H220. Extremely flammable gas.
H221. Flammable gas.
H222. Extremely flammable aerosol.
H225. Highly flammable liquid and vapour.
H229. Pressurised container: May burst if heated.
H280. Contains gas under pressure; may explode if heated.
H304. May be fatal if swallowed and enters airways.
H315. Causes skin irritation.
H319. Causes serious eye irritation.
H319. May cause drowsiness or dizziness.
H411. Toxic to aquatic life with long lasting effects.
H412. Harmful to aquatic life with long lasting effects.

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Germany: en Page: 12 / 12