

Product data sheet

PETEC Additive "Leck Stop Oil"



Description

PETEC additive "Leck Stop Oil"

engine oil additive for all engine, transmission and machine oils

For quick and permanent elimination of leaks in all oil circulation systems. Leck-Stop impregnates seals, makes them elastic again, makes them swell and thus eliminates the leak. Suitable for all oil circulation systems (e.g. engine, automatic and manual transmissions, differential, power steering, hydraulic system and many others) of cars, trucks, boats, tractors, motorcycles and many others. Leck-Stop can be added to the oil both in case of already existing leaks and as a preventive measure.

Note: Not suitable for motorcycle wet clutches!

Application:

Shake bottle well before use. Leck-Stop is added to the oil circuit to be sealed in a quantity of 3% of the total oil quantity, e.g. oil quantity 5 l = 150 ml Leck-Stop. The unit should then run for approx. 20 minutes so that the additive is distributed and reaches the areas to be sealed. In the course of the following 3 operating hours or after approx. 50 - 100 km, Leck-Stop takes effect, **150ml bottle**

Article number:	41132234
-----------------	----------

Original number:	80150
------------------	-------

EAN:	4013558801506
------	---------------

EVP:	50.15 €
------	----------------

Technical data

Design	additive
Range	engine
Main colour	yellow
Container type	bottle
Content	0.15 l
Type	vehicle, motorcycle, truck, commercial vehicle, small devices, oldtimer, marine
Fuel-efficiency (A-G)	fuel, diesel, gas
Weight	0.141 kg