

# Product data sheet

## BRENNABOR Trekking bike "T-44" Mod. 24



### Description

- 2x8-speed SHIMANO "Altus" derailleur and chain drive.
- Hydraulic Disc Brake.
- 75 mm suspension travel and Suspension Fork.
- 28" wheels.
- Fenders, Chain Guard, Hub Dynamo.
- Aluminum frame in silver blue / silverstar.
- Maximum system weight: 130 kg.

|                  |               |
|------------------|---------------|
| Article number:  | 02507036      |
| Original number: | 12316506-2602 |
| EAN:             | 4251507999403 |
| EVP:             | 999.00 €      |

| Technical data            |                                                  |
|---------------------------|--------------------------------------------------|
| Features                  | suspension fork, hub dynamo, chain guard, fender |
| Colour designation        | silver blue / silverstar                         |
| Main colour               | blue                                             |
| Secondary colour          | silver                                           |
| Travel                    | 75 mm                                            |
| Gender                    | ladies                                           |
| Gears                     | 16-speed                                         |
| Type                      | trekking bike                                    |
| Wheel size                | 28 "                                             |
| Material 1                | aluminium                                        |
| Frame height              | 50 cm                                            |
| Weight                    | 18.300 kg                                        |
| Stem length               | 100.0 mm                                         |
| Permissible system weight | 130 kg                                           |
| Toptube                   | 600 mm                                           |
| Wheel distance            | 1131 mm                                          |
| Seat tube                 | 500 mm                                           |
| Seat angle                | 73.0 °                                           |
| Steering tube             | 150 mm                                           |
| Steering tube angle       | 69.0 °                                           |