

## CONTEC Aluminium Rim "Exit"



### Description

A sturdy Aluminium Rim for building a classic fixed-gear wheel for 29" wheels with 32 spokes. Thanks to its hollow-chamber construction, this 6063 aluminum rim is particularly lightweight and sturdy. When assembled into a wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 21 mm, tires ranging from 35 to 62 mm in width fit on the rim. The single-eyelet nipple holes ensure additional durability of the rim by reducing friction between the Spoke Nipples and the rim and also preventing the nipples from grinding into the rim. The Exit Master Aluminium Rim is only suitable for wheels with disc brakes.

### Website



<https://www.contec-parts.com>

**Article number:** 03498173

**Original number:** 30002537

**EAN:** 4251971141179

**EVP:** 29.95 €

### Technical data

|                           |                                                                            |
|---------------------------|----------------------------------------------------------------------------|
| Design                    | doublewall                                                                 |
| Brake mounting            | disc - Center Lock, disc - 5-hole, disc - 6-hole, roller brake, drum brake |
| Brake compatibility rim   | disc                                                                       |
| ETRTO                     | 21-622                                                                     |
| Main colour               | black                                                                      |
| For wheel                 | yes                                                                        |
| Wheel size                | 28 / 29 "                                                                  |
| Material 1                | aluminium                                                                  |
| Weight                    | 0.536 kg                                                                   |
| Text wheel configurator   | suitable for E-bike                                                        |
| Valve type                | Sclaverand (SV)                                                            |
| Permissible system weight | 150 kg                                                                     |
| Spoke Hole                | easy eyelets                                                               |
| Hollow chamber shape      | symmetrical                                                                |
| Rim height                | 16 mm                                                                      |
| Rim inner width           | 21 mm                                                                      |
| Rim outer width           | 26 mm                                                                      |
| Spoke hole diameter       | for 2.00 mm                                                                |
| Eyelet color              | silver                                                                     |
| Effective Rim Diameter    | 608 mm                                                                     |
| max. spoke tension        | 1,200 N                                                                    |
| Brake track               | no                                                                         |
| Number of spoke holes     | 32 holes                                                                   |
| Rim model                 | Exit                                                                       |

# Product data sheet

## CONTEC Aluminium Rim "Exit"

