

The **NOMAD POWER 401** is a lithium-based power pack that combines 3 functions :

- **Booster for 12 V vehicles** (*motorbike, quad, light vehicle*).
- **Autonomous power supply for small electronic devices.**
- **Emergency lamp.**

## LITHIUM BATTERY BOOSTER

Its **lithium** battery ( $\text{LiCoO}_2$ ) gives it an exceptional power-to-size ratio (*starting current: 350 A*).

It starts vehicles equipped with a discharged 12 V battery (*liquid, gel, AGM, Start&Stop*) in a few seconds ( ⚠ *do not start Lithium  $\text{LiFePO}_4$  batteries with this booster, battery voltages not compatible*).

START									
									
12 V PETROL & DIESEL		5 > 70 Ah							

## SAFETY START

The **smart jump lead** protects both the battery and the vehicle's electronics:

- Anti-spark technology,
- Short circuit protection,
- Reverse polarity protection,
- Protection against excessive starting currents,
- Protection against booster temperature increases.

## MOBILE ENERGY SOURCE

Its storage capacity (*2.5 Ah*) gives it sufficient autonomy to meet the daily needs of staying connected (*telephone, tablet*).

Equipped with **2 USB ports** : 5 V / 9 V / 12 V - 2 A / 5 V - 2 A for recharging smartphone, tablet, GPS, etc.

## HIGH BRIGHTNESS ASSIST LAMP

Auxiliary light (*1 led*) with 3 lighting modes: normal, strobe, SOS.

## LCD DISPLAY

The **NOMAD POWER 401** is equipped with an LCD display that gives information on :

- the % of charge of the internal battery.
- the different input and output ports used.

## A SMART PRODUCT

**Lightweight** (*320g*) and **compact**, it will ideally find its place in a vehicle's glove box/tray as well as in a suitcase.



LCD screen



Supplied with case  
+ accessories



Smart jump lead



Multiconnectors  
USB cable



USB-C / USB-C  
charging cable

















Charger unit *optional*



087101 USB charger 15 W



🇬🇧 087354 USB charger 15 W

STARTING						EQUIPMENT				INPUT / OUTPUT				POWER BANK	LED	DIMENSIONS	
Lithium			I			SMART CABLE	CABLES 			INPUT 	OUTPUT 						
Capacity per cell	Type	Full charge	Start	Cranking CC	Peak Battery		USB-C	MICRO USB Type B	Lightning			12 V	15 V				
2.5 Ah 37 Wh	LiCoO <sub>2</sub>	3 h	350 A	700 A	900 A					5V - 2 A	2  5V - 2.1 A 5/9/12V - 2 A	—	—		3 modes : Light SOS SPOT	14.5 x 8.5 x 3	0.320