

Printing date 07.01.2025 Version: 2.01 (replaces version 2.00) Revision: 07.01.2025

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: SONAX Antifreeze+Clear View to -18°C Sweet Home

Article number:

01363410, 01364000, 01364410, 01365050

**UFI:** 3SR5-X0TV-900K-14TK

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Car care product

Anti-Freeze and de-icing products

Detergents

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.

# 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

#### Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

**United Kingdom:** 

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

**United Kingdom: 0344 892 0111 (UK NPIS)** 

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

# SECTION 2: Hazards identification

# 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

Additional information:

Sustained combustibility test ISO 9038/UN manual of tests and criteria (32.5.2):

no self-sustained combustion

#### 2.2 Label elements

# Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

# Hazard pictograms



## Signal word Warning

# Hazard-determining components of labelling:

Cinnamal

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)



Printing date 07.01.2025 Version: 2.01 (replaces version 2.00) Revision: 07.01.2025

Trade name: SONAX Antifreeze+Clear View to -18°C Sweet Home

(Contd. of page 1)

P102 Keep out of reach of children. P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 2.3 Other hazards

# Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

#### vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

### Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

**Description:** Aqueous formulation of alcohol, glycol and tensides.

Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol	15-<20%
CAS: 107-21-1 EINECS: 203-473-3 Reg.nr.: 01-2119456816-28-xxxx	ethanediol STOT RE 2, H373; 🗘 Acute Tox. 4, H302	5-<10%
CAS: 56-81-5 EINECS: 200-289-5	glycerol substance with a Community workplace exposure limit	5-<10%
CAS: 104-55-2 EINECS: 203-213-9	Cinnamal  ↑ Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.01 %	<0.1%

Regulation (EC) No 648/2004 on detergents / Labelling for contents	
anionic surfactants	<5%
perfumes (EUGENOL, CINNAMAL)	

Additional information: For the wording of the listed hazard phrases refer to section 16.

# SECTION 4: First aid measures

# 4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air.

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

#### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

# After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

sensitization Allergic reactions

(Contd. on page 3)



Printing date 07.01.2025 Version: 2.01 (replaces version 2.00) Revision: 07.01.2025

Trade name: SONAX Antifreeze+Clear View to -18°C Sweet Home

(Contd. of page 2)

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

# SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

#### Suitable extinguishing agents:

Water spray

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

For safety reasons unsuitable extinguishing agents: Water with full jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

# 5.3 Advice for firefighters

#### Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

#### Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### SECTION 6: Accidental release measures

# 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation For non-emergency personnel

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wear protective clothing.

For emergency responders Wear protective equipment. Keep unprotected persons away.

### 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

# 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

## 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

**7.1 Precautions for safe handling** No special precautions are necessary if used correctly. **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.

# 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground. Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

### Further information about storage conditions:

Keep container tightly sealed.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

(Contd. on page 4)



Revision: 07.01.2025 Printing date 07.01.2025 Version: 2.01 (replaces version 2.00)

Trade name: SONAX Antifreeze+Clear View to -18°C Sweet Home

(Contd. of page 3)

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:			
CAS: 64-17-5 ethan	CAS: 64-17-5 ethanol		
WEL (Great Britain)	WEL (Great Britain) Long-term value: 1920 mg/m³, 1000 ppm		
OEL (Ireland)	Short-term value: 1000 ppm		
CAS: 107-21-1 etha	CAS: 107-21-1 ethanediol		
WEL (Great Britain)	Short-term value: 104** mg/m³, 40** ppm Long-term value: 10* 52** mg/m³, 20** ppm Sk *particulate **vapour		
IOELV (EU)	Short-term value: 104 mg/m³, 40 ppm Long-term value: 52 mg/m³, 20 ppm Skin		
OEL (Ireland)	Short-term value: 104 mg/m³, 40 ppm Long-term value: 52 mg/m³, 20 ppm Skin, IOELV		
CAS: 56-81-5 glyce	CAS: 56-81-5 glycerol		
WEL (Great Britain)	Long-term value: 10 mg/m³		
OEL (Ireland)	Long-term value: 10 mg/m³		

# Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2024 CoP for the Safety, Health and Welfare at Work

IOELV (EU): (EU) 2019/1831

DNELs			
CAS: 64-1	CAS: 64-17-5 ethanol		
Oral	DNEL	87 mg/kg (consumer) (long-term exposure - systemic effects)	
Dermal	DNEL	206 mg/kg bw/day (consumer) (long-term exposure - systemic effects)	
		343 mg/kg bw/day (worker) (lon-term exposure - systemic effects)	
Inhalative	DNEL	950 mg/m³ (consumer) (acute short-tem exposure - local effects)	
		1,900 mg/m³ (worker) (acute short-tem exposure - local effects)	
	DNEL	114 mg/m³ (consumer) (long-term exposure - systemic effects)	
		950 mg/m³ (worker) (long-term exposure - systemic effects)	
CAS: 107	-21-1 e	thanediol	
Dermal	DNEL	53 mg/kg bw/day (consumer) (long term (chronic) / systemic)	
		106 mg/kg bw/day (worker) (long term (chronic) / systemic)	
Inhalative	DNEL	7 mg/m³ (consumer) (long term (chronic) / local)	
		35 mg/m³ (worker) (long term (chronic) / local)	
51150	•		

#### **PNECs**

### CAS: 64-17-5 ethanol

PNEC 580 mg/l (sewage plant) 0.96 mg/l (water (fresh water)) 0.79 mg/l (water (sea water)) PNEC 3.6 mg/kg (sediment (fresh water))

# CAS: 107-21-1 ethanediol

0.63 mg/kg (soil)

#### PNEC | 199.5 mg/l (STP)

10 mg/l (water (intermittent release))

10 mg/l (water (fresh water))



Revision: 07.01.2025 Printing date 07.01.2025 Version: 2.01 (replaces version 2.00)

Trade name: SONAX Antifreeze+Clear View to -18°C Sweet Home

(Contd. of page 4)

1 mg/l (water (sea water))

PNEC 1.53 mg/kg (gro)

37 mg/kg (sediment (fresh water)) (dry weight) 3.7 mg/kg (sediment (sea water)) (dry weight)

Additional information: The lists valid during the making were used as basis.

#### 8.2 Exposure controls

#### Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to

# Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Hand protection Protective gloves

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

**IEN 3741** 

Penetration time of glove material Value for the permeation: Level 6 (≥480min)

Eye/face protection Not required in normal cases

# SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

Physical state Fluid Colour: Orange Odour: Aromatic Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

78-200 °C **Flammability** Flammable.

Lower and upper explosion limit

Lower: 3.5 Vol % (CAS: 64-17-5 ethanol) 15 Vol % (CAS: 64-17-5 ethanol) Upper:

Flash point: 36 °C (DIN 51755) Decomposition temperature: Not determined. 6-7

pH at 20 °C

Viscosity:

Kinematic viscosity at 20 °C 10-15 s (DIN 53211/4)

Dynamic: Not determined. Solubility Fully miscible. water:

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: 0.99-1 q/cm3 Not determined. Vapour density

9.2 Other information Sustained combustibility test ISO 9038/UN manual of

tests and criteria (32.5.2):

no self-sustained combustion

(Contd. on page 6)



Printing date 07.01.2025 Version: 2.01 (replaces version 2.00) Revision: 07.01.2025

Trade name: SONAX Antifreeze+Clear View to -18°C Sweet Home

(Contd. of page 5)

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Ignition temperature:Not determined.Explosive properties:Not determined.Change in conditionNot determined.Evaporation rateNot determined.

Information with regard to physical hazard classes

ExplosivesVoidFlammable gasesVoidAerosolsVoidOxidising gasesVoidGases under pressureVoid

Flammable liquids Sustained combustibility test ISO 9038/UN manual of

tests and criteria (32.5.2):

no self-sustained combustion

Flammable solids Void
Self-reactive substances and mixtures Void
Pyrophoric liquids Void
Pyrophoric solids Void
Self-heating substances and mixtures Void
Substances and mixtures, which emit flammable

Substances and mixtures, which emit flammable gases in contact with water

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Desensitised explosives

Void

Void

Void

Void

Void

# SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions known.
- 10.2 Chemical stability Stable under normal conditions.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	LD/LC50 values relevant for classification:		
CAS: 64-1	CAS: 64-17-5 ethanol		
Oral	LD50	10,470 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
Inhalative	LC50 / 4h	>20 mg/l (mouse)	
		38 mg/l (rat)	
CAS: 107-	CAS: 107-21-1 ethanediol		
Oral	LD50	7,712 mg/kg (rat)	
Dermal	LD50	>3,500 mg/kg (mouse)	
Inhalative	LC50 / 6 h	>2.5 mg/l (rat)	

(Contd. on page 7)



Printing date 07.01.2025 Version: 2.01 (replaces version 2.00) Revision: 07.01.2025

Trade name: SONAX Antifreeze+Clear View to -18°C Sweet Home

(Contd. of page 6)

CAS: 104-55-2 Cinnamal

Oral LD50 2,220 mg/kg (rat)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Additional toxicological information:

Repeated dose toxicity

CAS: 64-17-5 ethanol

Oral NOAEL 1,760 mg/kg (rat) (OECD 408, 90d, target organ: liver)

### 11.2 Information on other hazards

#### Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

# **SECTION 12: Ecological information**

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aqua		

LC50 / 48h 8,140 mg/l (Leuciscus idus)
EC50 / 48h >10,000 mg/l (Daphnia magna)
EC50 / 72h 275 mg/l (Chlorella vulgaris)

## CAS: 107-21-1 ethanediol

LC50 / 96h | 72,860 mg/l (Pimephales promelas)

EC20 / 0.5 h >1,995 mg/l (activated sludge)

EC50 / 48h | >100 mg/l (Daphnia magna)

EC50 / 96 h 6,500-13,000 mg/l (Pseudokirchneriella subcapitata) NOEC / 7 d 8,590 mg/l (Ceriodaphnia Dubia) (EPA 600/4-89/001)

15,380 mg/l (Pimephales promelas) (EPA 600/4-89/001)

# 12.2 Persistence and degradability

The surface-active substances contained in the product meet the requirement of the EU Detregent Regulation (EC/648/2004) for ultimate biodegradability for surfactants in detergents.

# 12.3 Bioaccumulative potential

CAS: 107-21-1 ethanediol

log POW <1.36

12.4 Mobility in soil No further relevant information available.

# 12.5 Results of PBT and vPvB assessment

#### PBT:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

#### vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

(Contd. on page 8)



Printing date 07.01.2025 Version: 2.01 (replaces version 2.00) Revision: 07.01.2025

Trade name: SONAX Antifreeze+Clear View to -18°C Sweet Home

(Contd. of page 7)

#### 12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

# SECTION 13: Disposal considerations

# 13.1 Waste treatment methods

Not classified as hazardous waste according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

#### European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

20 01 30 detergents other than those mentioned in 20 01 29

15 01 02 plastic packaging

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport info	ormation
14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR/RID/ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR/RID/ADN, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
Transport/Additional information	: Sustained combustibility test ISO 9038/UN manual of tests and criteria (32.5.2): no self-sustained combustion
UN "Model Regulation":	Void

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Poisons Act

#### Regulated explosives precursors

None of the ingredients is listed.

# Regulated poisons

None of the ingredients is listed.

### Reportable explosives precursors

None of the ingredients is listed.

(Contd. on page 9)



Printing date 07.01.2025 Version: 2.01 (replaces version 2.00) Revision: 07.01.2025

Trade name: SONAX Antifreeze+Clear View to -18°C Sweet Home

(Contd. of page 8)

#### Reportable poisons

None of the ingredients is listed.

European Directives:

Directive 2010/75/EU (VOC) 24.81 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

#### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

### National regulations:

### Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

### Classification according to Regulation (EC) No 1272/2008

Skin sensitisation | The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Date of previous version: 22.08.2024 Version number of previous version: 2.00

#### Abbreviations and acronyms:

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 \* Data compared to the previous version altered.