

Product data sheet

VICTORIA Electric trekking bike "TRESALO 15" (#1)



Description

The Victoria TRESALO 15 hub gear model is a solid everyday and touring partner. Specially designed for use on pedelecs, the Shimano "Nexus" 5-speed Hub is available with either coaster or freewheel. The smart Bosch system more than adequately supports your pedaling performance thanks to the new Performance engine and the "PowerTube 625" Battery.

The "Kiox 300" color display, which is 1A readable even in the dark, provides useful information about the current route. If the available information is not sufficient, additional features can be obtained via the free eFlow app. Coupled with other navigation apps, such as Komoot or Strava, this provides a whole new riding experience with the new bike.

The TRESALO models with integrated PowerTube batteries are designed by us with a stable and stiff chassis. The riding position is - as you would expect from a Victoria - more upright and comfort-oriented than overly sporty and stretched.

As with all new Victoria developments, the batteries integrated in the down tube can be removed upwards. This means that there is no need for a catch, as is the case with downward removal. However, in view of the large capacity and the associated battery weight, we recommend charging on the bike instead, as it is simply more convenient.

Website



<https://www.victoria-bikes.com>

Article number: 02920121

Original number: KHA250121

EAN: 4251971165939

EVP: **3799.00 €**

Technical data

Battery capacity	625.0 Wh
Features	suspension fork, suspension seatpost, frame lock, system carrier, chain guard, electronic sliding aid, fender
Colour designation	airstream silver
Main colour	grey
Secondary colour	black
Travel	63 mm
Gender	gents
Gears	5-speed
Type	trekking bike
Wheel size	28 "
Material 1	aluminium
Engine power	250 W
Frame height	50 cm
Weight	29.800 kg
Permissible system weight	140 kg
Chainstay	490 mm
Toptube	584 mm
Reach	390 mm
Seat tube	500 mm
Seat angle	73.0 °
Stack	634 mm
Steering tube	155 mm
Steering tube angle	70.0 °