Product data sheet

VICTORIA Electric trekking bike "Cysalo 5" (#1)



Website

https://www.victoria-bikes.com

Article number:	02921018
Original number:	4251971178953
EAN:	4251971178953
EVP:	**2499.00 €**

Description

City e-bike for everyday use. The CYSALO 5 is the perfect city bike for leisurely rides in the city and out in the countryside. With its sturdy build and reliable components, it takes you safely and comfortably through your daily routine. The MIK System carrier offers practical options for attaching bags or baskets and ensures that you always have everything with you.

Comfort and Functionality
The Suspension Fork with 63 mm of travel guarantees a smooth ride, even on bumpy paths. The adjustable Stem and 640 mm-wide Handlebars allow for an ergonomic riding position that makes cycling particularly enjoyable. The reliable Shimano disc brakes front and rear ensure safety in all weather conditions.

Technical Specifications
The CYSALO 5 features a Shimano Nexus 7-speed hub gear system and an Active Plus drive system, which provide smooth and powerful assistance. The PowerTube 545 battery offers enough power for long rides. The Intuvia 100 display shows all important information at a glance, and the 60-lux lighting from Herrmanns ensures optimal visibility in traffic.

Target Audience
The CYSALO 5 is your ideal city bike if you're looking for a reliable, comfortable, and affordable companion for everyday use. With its straightforward features and proven quality, it's the right choice for everyday and occasional riders who value good value for the money.
Gear ratio range: 244%

,

Technical data

Battery capacity	400.0 Wh
Features	suspension fork, system carrier, chain guard, electronic sliding aid, fender
Torque	50 Nm
Colour designation	slate grey matt
Main colour	grey
Travel	63 mm
Gender	ladies
Gears	7-speed
Type	trekking bike
Wheel size	28 "
Material	aluminium
Engine power	250 W
Frame height	52 cm
Weight	28.200 kg
Stem length	90.0 mm
Permissible system weight	140 kg
Chainstay	510 mm
Toptube	605 mm
Wheel distance	1158 mm
Reach	394 mm
Seat tube	520 mm
Seat angle	74.0 °
Stack	645 mm
Steering tube	160 mm
Steering tube angle	70.0 °

This product data sheet is based on the information available at the time of generation. Subsequent changes to prices, technical specifications, or product information are possible. The current details provided with the item are authoritative.

Date of generation: 05.11.2026